

### Features

- 1.35V–5V operating voltage
- 64-note memory
- Volume control capability
- On-chip envelope modulator
- Low stand-by current
- Built-in oscillator and pre-amplifier circuit
- A piezo or magnetic buzzer can be driven by connecting an NPN transistor


### General Description

The UM338X series is a mask programmed simple generator implemented in the CMOS technology. The melody signal is generated according to the previously programmed tone rhythm and tempo information. By properly modifying the envelope of the electric signal, sound effect of piano or organ may be generated. The device


also includes a pre-amplifier which provides simple interface to the drive circuit.

The UM338X series is intended for application such as toys, music box, melody clock/timers and telephones.

### Pin Configuration



### Block Diagram



**Absolute Maximum Ratings\***

DC Supply Voltage .....	-0.3V to 5V
Input/Output Voltage.....	$V_{SS} - 0.2V$ to $V_{DD} + 0.2V$
Operating Ambient Temperature.....	-20°C to +65°C
Storage Temperature.....	-55°C to +125°C

**\*Comments**

Stress above those listed under "Absolute Maximum Rating" may cause permanent damage to the device. These are stress ratings only. Functional operation of this device at these or any other conditions above those indicated in the operational sections of this specification is not implied and exposure to absolute maximum rating conditions for extended periods may affect device reliability.


**Electrical Characteristics**

( $V_{DD} = 1.5V$ ,  $V_{SS} = 0V$ ,  $T_A = 25^\circ C$ , unless otherwise specified.)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Stand-by Current	$I_{STB}$	OSC HALTING	0.1	0.1	10	$\mu A$
High Level Input Voltage	$V_{IH}$	-	$V_{DD} - 0.3$	-	$V_{DD}$	V
Low Level Input Voltage	$V_{IL}$	$V_{IH} = V_{DD}$	$V_{SS}$	-	$V_{SS} + 0.3$	$\mu A$
High Level Input Current	$I_{OH}$	$V_{OH} = 0.8V$	1.5	3	6	$\mu A$
Output Current OP1 Terminal	$I_{OL}$	$V_{OL} = 0.8$	200	-	1200	$\mu A$
Output Current OP2 Terminal	$I_{OH}$	$V_{OH} = 0.7V$	200	-	1200	$\mu A$

**Pin Description**

Pin No.	Designation	Description
1	OSC1	PIN 1 to PIN 3 connected as an RC oscillator
2	OSC2	
3	OSC3	
4	CE	Chip enabled when $CE = V_{IH}$ Chip disabled when $CE = V_{IL}$
5	RPT	Song repeated if $RPT = V_{IH}$ Song stopped as melody ends if $RPT = V_{IL}$
6	NC	No connection
7	$V_{SS}$	Power supply negative
8	ENV	Envelope circuit terminal
9	MTO	Modulated tone signal output
10	NC	Same as pin 6
11	OP1	Pre-amplifier output
12	OP2	
13	MTI	Modulated tone signal input to the pre-amplifier
14	$V_{DD}$	Power supply positive

**Bonding Diagram**


Pad No.	Designation	X	Y
1	OSC1	-320.04	980.44
2	OSC2	-624.84	980.44
3	OSC3	-929.64	855.98
4	CE	-929.64	63.50
5	RPT	-929.64	-850.90
6	NC	-685.80	-980.44
7	VSS	-226.06	-980.44
8	ENV	48.26	-980.44
9	MTO	904.24	-980.44
10	NC	904.24	-670.56
11	OP1	904.24	-388.62
12	OP2	904.24	419.10
13	MT1	904.24	980.44
14	VDD	441.96	980.44

**Function Description**
**Oscillation and Control Circuit**

The resistor  $R_1$  and capacitor  $C_1$  are connected externally for setting the frequency (typically 50KHZ). Addition of resistor  $R_5$  in series with input inverter is to make circuit insensitive to the variation of the supply voltage. Under stand-by condition (CE is low) the operation of the built-in oscillating circuit is inhibited. As soon as a high level signal enters into the CE input, the circuit starts oscillating. Since the oscillation frequency is used as a time base to the tone generator and the rhythm generator, its accuracy will affect the quality of the music.

**Melody ROM**

The mask ROM can memorize 64 words with 7 bits each. Of these, 4 bits are used for controlling the tone generator and 3 bits are used for controlling the rhythm generator.


Usually there are only 63 words available for the melody programming since 1 word is used for the control of automatic stop.

**Tone Generator**

The tone generator is a programmed divider. It divides the base frequency by 72 to 254 following the data stored in the melody ROM. The central "Do" is 263.16Hz if the base frequency is 50KHz; the scale range is from 5 to 4.


**Enveloping Circuit and Modulator**

The tone signal is put through an enveloping circuit and the output waveform shown in Figure 1 is produced.


**Figure 1. Waveform of modulated tone output (MTO)**

The enveloping circuit is shown in Figure 2. Proper selection of  $C_2$ ,  $R_2$  &  $R_4$  can produce envelops of desired

charging and discharging time.




**Figure 2. The enveloping circuit**

### Pre-amplifier

The equivalent circuit of the pre-amplifier is shown in Figure 3. Feedback resistor  $R_5$  must be connected to obtain proper bias of the pre-amplifier stage. In the stand-by


state the pre-amplifier is disabled,  $OP_1$  is pulled up to  $V_{DD}$  and  $OP_2$  is pulled down to  $V_{SS}$ .




**Figure 3. Pre-amplifier circuit**

### Typical Application

#### SIMPLE APPLICATION CIRCUIT USING MAGNETIC BUZZER



**TYPICAL APPLICATION CIRCUIT USING SPEAKER**

**Song Series List**

- |          |   |
|----------|---|
| UM3381   | Jingle Bells  |
| UM3381-1 | A Medley of Jingle Bells, Santa Claus is Coming to Town and We Wish You a Merry Christmas |
| UM3381-2 | A Medley of Silent Night and The First Noel   |
| UM3381-3 | A Medley of Jingle Bells, Deck the Halls and Joy to the World                             |
| UM3382   | A Medley of Three Blind Mice and Farmer in the Dell                                       |
| UM3382-1 | Lullaby (Brahms)  |
| UM3382-2 | Counting the Frogs; (Chinese children's song)   |
| UM3382-3 | A Medley of Happy Birthday and For He is a Jolly Good Fellow                              |
| UM3383   | Blue Bells of Scotland  |
| UM3383-1 | Beethoven Symphony No. 9  |
| UM3383-2 | Home Sweet Home   |
| UM3383-3 | Camel Train   |