



Triple Line Receiver (High Speed)

**ELECTRICALLY TESTED PER:
MPG 10616**

The 10616 is a high speed triple differential amplifier designed for use in sensing differential signals over long lines. The base bias supply (V_{BB}) is made available at pin 11 make the device useful as a Schmitt trigger, or in other application where a stable reference voltage is necessary.

Active current sources provide the 10616 with excellent common mode noise rejection. If any amplifier in a package is not used, one input of that amplifier must be connected to V_{BB} (pin 11) to prevent upsetting the current source bias network.

Complementary outputs are provided to allow driving twisted pair lines, to enable cascading of several amplifiers in a chain, or simply to provide complement outputs of the input logic function.

- 150 mW Max/Pkg (No Load)
- $t_{pd} = 2.0$ ns typ (All Output Loaded)
- $t_r, t_f = 2.0$ ns typ (20% - 80%)

PIN ASSIGNMENTS

| FUNCTION | DIL | FLATS | LCC | BURN-IN (CONDITION C) |
|-------------------|-----|-------|-----|--------------------------|
| V_{CC1} | 1 | 5 | 2 | GND |
| $\overline{A}OUT$ | 2 | 6 | 3 | 51Ω to V_{TT} |
| AOUT | 3 | 7 | 4 | 51Ω to V_{TT} |
| $\overline{A}IN$ | 4 | 8 | 5 | GND |
| A _{IN} | 5 | 9 | 7 | V_{BB} |
| $\overline{B}OUT$ | 6 | 10 | 8 | 51Ω to V_{TT} |
| BOUT | 7 | 11 | 9 | 51Ω to V_{TT} |
| V_{EE} | 8 | 12 | 10 | V_{EE} |
| $\overline{B}IN$ | 9 | 13 | 12 | GND |
| B _{IN} | 10 | 14 | 13 | V_{BB} |
| V_{BB} | 11 | 15 | 14 | V_{BB} |
| $\overline{C}IN$ | 12 | 16 | 15 | GND |
| C _{IN} | 13 | 1 | 17 | V_{BB} |
| $\overline{C}OUT$ | 14 | 2 | 18 | 51Ω to V_{TT} |
| COUT | 15 | 3 | 19 | 51Ω to V_{TT} |
| V_{CC2} | 16 | 4 | 20 | GND |

BURN - IN CONDITIONS:

$V_{TT} = -2.0$ V MAX/ -2.2 V MIN

$V_{EE} = -5.7$ V MAX/ -5.2 V MIN

NOTES:

1. V_{BB} to be used to supply bias to the 10616 only and bypassed (when used) with $0.01 \mu F$ to $0.1 \mu F$ capacitor.
2. When the input pin with the bubble goes positive, the output goes positive.

Military 10616




AVAILABLE AS:


- 1) JAN: N/A
 - 2) SMD: N/A
 - 3) 883: 10616/BXAJC
- X = CASE OUTLINE AS FOLLOWS:


PACKAGE: CERDIP: E
CERFLAT: F
LCC: 2

The letter "M" appears before the slash on LCC.



LOGIC DIAGRAM





NOTES

1. All unused outputs loaded 100 Ω to ground.
2. V_{IN} has the following characteristics:
 - a) pulse width = 20 ns.
 - b) frequency = 1.0 MHz.
 - c) t_r and t_f = 1.5 ns ± 0.2 ns.




Figure 1. Switching Test Circuit and Waveforms

10616 QUIESCENT LIMIT TABLE *

* ELECTRICAL CHARACTERISTICS

Each MECL 10K series circuit has been designed to meet the dc specifications shown in the test table, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear fpm is maintained. Outputs are terminated through a 100 Ω resistor to - 2.0 volts.

| Test Temperature | Test Voltage Values (Volts) | | | | | | |
|--------------------------|-----------------------------|-----------------|------------------|------------------|--------|--------|----------------------------------|
| | V _{IH} | V _{IL} | V _{IH1} | V _{IL1} | PS1 | PS2 | V _{CB} /V _{EE} |
| T _A = 25 °C | - 0.78 | - 1.85 | - 1.105 | - 1.475 | + 1.11 | + 0.31 | - 5.2 |
| T _A = 125 °C | - 0.63 | - 1.82 | - 1.000 | - 1.400 | + 1.24 | + 0.36 | - 5.2 |
| T _A = - 55 °C | - 0.88 | - 1.92 | - 1.255 | - 1.510 | + 1.01 | + 0.28 | - 5.2 |

| Symbol | Parameter | Limits | | | | | | Units | TEST VOLTAGE APPLIED TO PINS BELOW | | | | | | | | |
|------------------|-------------------------------|------------|------------|-------------|-------------|------------|-----------------|-------|---|---------------------|------------------|-----------------|---------------------|-----------------|-----------------|----------|---------------------|
| | | + 25 °C | | + 125 °C | | - 55 °C | | | Pinouts referenced are for DIL package, check Pin Assignments V _{BB} to pin 11, V _{CC} = 0 V, Output Load = 100 Ω to - 2.0 V | | | | | | | | |
| | | Subgroup 1 | Subgroup 2 | Subgroup 1 | Subgroup 2 | Subgroup 3 | V _{IH} | | V _{IL} | V _{IH1} | V _{IL1} | V _{BB} | V _{CB} | V _{EE} | V _{CC} | P. U. T. | |
| | Functional Parameters: | | | | | | | | | | | | | | | | |
| V _{OH} | High Output Voltage | Min - 0.93 | Max - 0.78 | Min - 0.825 | Max - 0.63 | Min - 1.08 | Max - 0.88 | V | 4, 5, 9, 12, 13 | 4, 5, 9, 12, 13 | | | | | 8 | 1, 16 | 2, 3, 6, 7, 14, 15 |
| V _{OL} | Low Output Voltage | Min - 1.85 | Max - 1.62 | Min - 1.82 | Max - 1.545 | Min - 1.92 | Max - 1.655 | V | 4, 5, 9, 12, 13 | 4, 5, 9, 12, 13 | | | | | 8 | 1, 16 | 2, 3, 6, 7, 14, 15 |
| V _{OL1} | Low Output Voltage | | Max - 1.60 | | Max - 1.525 | | Max - 1.635 | V | | | | | 4, 5, 9, 10, 12, 13 | 4, 9, 13, 14 | 8 | 1, 16 | 2, 3, 6, 7, 14, 15 |
| V _{OH1} | High Output Voltage | Min - 0.95 | | Min - 0.845 | | Min - 1.10 | | V | | | | | 4, 5, 9, 10, 12, 13 | 4, 9, 13, 14 | 8 | 1, 16 | 2, 3, 6, 7, 14, 15 |
| V _{BB} | Reference Bias Supply Voltage | Min - 1.35 | Max - 1.23 | Min - 1.24 | Max - 1.12 | Min - 1.44 | Max - 1.32 | V | 4, 9, 12 | 5, 10, 13 | | | | | 8 | 1, 16 | 11 |
| I _{CB0} | Open Collector Input Current | Min - 1.0 | | Min - 1.0 | | Min - 1.5 | | μA | 4, 7, 9, 12, 14 | | | | | 5, 10, 13 | 8 | 1, 16 | 4, 5, 9, 10, 12, 13 |
| I _{IH} | Input Current High | | Max 115 | | Max 195 | | Max 195 | μA | 4, 5, 9, 10, 12, 13 | 4, 5, 9, 10, 12, 13 | | | | | 8 | 1, 16 | 4, 5, 9, 10, 12, 13 |
| I _{EE} | Power Supply Drain Current | Min - 25 | | Min - 28 | | Min - 28 | | mA | | 5, 10, 13 | | | | | 8 | 1, 16 | 8 |

10616 QUIESCENT LIMIT TABLE *

* ELECTRICAL CHARACTERISTICS

Each MECL 10K series circuit has been designed to meet the dc specifications shown in the test table, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow greater than 500 linear fpm is maintained. Outputs are terminated through a 100 Ω resistor to - 2.0 volts.

| Test Temperature | Test Voltage Values (Volts) | | | | | | | | | |
|--------------------------|-----------------------------|-----------------|------------------|------------------|--------|--------|---------|-------|--|--|
| | V _{IH} | V _{IL} | V _{IH1} | V _{IL1} | PS1 | PS2 | VCB/VEE | VEEL | | |
| T _A = 25 °C | - 0.78 | - 1.85 | - 1.105 | - 1.475 | + 1.11 | + 0.31 | - 5.2 | - 3.2 | | |
| T _A = 125 °C | - 0.63 | - 1.82 | - 1.000 | - 1.400 | + 1.24 | + 0.36 | - 5.2 | - 3.2 | | |
| T _A = - 55 °C | - 0.88 | - 1.92 | - 1.255 | - 1.510 | + 1.01 | + 0.28 | - 5.2 | - 3.2 | | |

| Symbol | Parameter | Limits | | | | Units | TEST VOLTAGE APPLIED TO PINS BELOW | | | | | | | | |
|------------------------|-------------------|------------|-----|-------------|-----|-------------|------------------------------------|-----------------|--|------------------|------------------|-------|-----|---------|--------------------|
| | | + 25 °C | | + 125 °C | | | - 55 °C | | Pinouts referenced are for DIL package, check Pin Assignments V _{CC} = 2.0 V, Output Load = 100 Ω to GND | | | | | | |
| Functional Parameters: | | Subgroup 9 | | Subgroup 10 | | Subgroup 11 | | V _{IH} | V _{IL} | V _{IH1} | V _{IL1} | PS1 | PS2 | VCB/VEE | VEEL |
| t _{RLH} | Rise Time | 1.0 | 2.5 | 1.0 | 2.9 | 1.0 | 2.7 | ns | 4, 9, 12 | 2, 14 | 5, 10, 13 | 1, 16 | 8 | 8 | 2, 3, 6, 7, 14, 15 |
| t _{FHL} | Fall Time | 1.0 | 2.5 | 1.0 | 2.9 | 1.0 | 2.7 | ns | 4, 9, 12 | 2, 14 | 5, 10, 13 | 1, 16 | 8 | 8 | 2, 3, 6, 7, 14, 15 |
| t _{pHL} | Propagation Delay | 1.0 | 2.5 | 1.0 | 2.9 | 1.0 | 2.7 | ns | 4, 9, 12 | 2, 14 | 5, 10, 13 | 1, 16 | 8 | 8 | 2, 3, 6, 7, 14, 15 |
| t _{pLH} | Propagation Delay | 1.0 | 2.5 | 1.0 | 2.9 | 1.0 | 2.7 | ns | 4, 9, 12 | 2, 14 | 5, 10, 13 | 1, 16 | 8 | 8 | 2, 3, 6, 7, 14, 15 |

PACKAGE OUTLINE DIMENSIONS


A letter suffix to the MECL logic function part number is used to specify the package style (see drawings below). See appropriate selector guide for specific packaging available for a given device type.

| <p>L SUFFIX CERAMIC PACKAGE CASE 620-09</p> <table border="1"> <thead> <tr> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>DIM</th> <th>MIN MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr><td>A</td><td>19.95 19.81</td><td>0.790</td><td>0.790</td></tr> <tr><td>B</td><td>6.32 6.30</td><td>0.248</td><td>0.275</td></tr> <tr><td>C</td><td>4.06 5.00</td><td>0.160</td><td>0.200</td></tr> <tr><td>D</td><td>0.38 0.51</td><td>0.015</td><td>0.020</td></tr> <tr><td>F</td><td>1.40 1.65</td><td>0.055</td><td>0.065</td></tr> <tr><td>G</td><td>2.54 BSC</td><td>0.100 BSC</td><td></td></tr> <tr><td>H</td><td>0.51 1.14</td><td>0.020</td><td>0.045</td></tr> <tr><td>J</td><td>0.20 0.30</td><td>0.008</td><td>0.012</td></tr> <tr><td>K</td><td>3.18 4.06</td><td>0.125</td><td>0.160</td></tr> <tr><td>L</td><td>2.27 2.27</td><td>0.290</td><td>0.310</td></tr> <tr><td>M</td><td>— 15°</td><td>— 15°</td><td></td></tr> <tr><td>N</td><td>0.51 1.02</td><td>0.020</td><td>0.040</td></tr> </tbody> </table> <p>NOTES: 1. LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION. 2. PACKAGE INDEX: NOTCH IN LEAD NOTCH IN CERAMIC OR INK DOT. 3. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.</p> | MILLIMETERS | | INCHES | | DIM | MIN MAX | MIN | MAX | A | 19.95 19.81 | 0.790 | 0.790 | B | 6.32 6.30 | 0.248 | 0.275 | C | 4.06 5.00 | 0.160 | 0.200 | D | 0.38 0.51 | 0.015 | 0.020 | F | 1.40 1.65 | 0.055 | 0.065 | G | 2.54 BSC | 0.100 BSC | | H | 0.51 1.14 | 0.020 | 0.045 | J | 0.20 0.30 | 0.008 | 0.012 | K | 3.18 4.06 | 0.125 | 0.160 | L | 2.27 2.27 | 0.290 | 0.310 | M | — 15° | — 15° | | N | 0.51 1.02 | 0.020 | 0.040 | <p>L SUFFIX CERAMIC PACKAGE CASE 623-05 (LW SUFFIX FOR MC10H181 ONLY)</p> <table border="1"> <thead> <tr> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>DIM</th> <th>MIN MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr><td>A</td><td>31.24 32.77</td><td>1.230</td><td>1.290</td></tr> <tr><td>B</td><td>12.70 15.49</td><td>0.500</td><td>0.610</td></tr> <tr><td>C</td><td>4.06 5.59</td><td>0.160</td><td>0.220</td></tr> <tr><td>D</td><td>0.41 0.51</td><td>0.016</td><td>0.020</td></tr> <tr><td>F</td><td>1.77 1.92</td><td>0.050</td><td>0.060</td></tr> <tr><td>G</td><td>2.54 BSC</td><td>0.100 BSC</td><td></td></tr> <tr><td>J</td><td>0.20 0.30</td><td>0.008</td><td>0.012</td></tr> <tr><td>K</td><td>3.18 4.06</td><td>0.125</td><td>0.160</td></tr> <tr><td>L</td><td>15.24 BSC</td><td>0.600 BSC</td><td></td></tr> <tr><td>M</td><td>0° 15°</td><td>0° 15°</td><td></td></tr> <tr><td>N</td><td>0.51 1.27</td><td>0.020</td><td>0.050</td></tr> </tbody> </table> <p>NOTES: 1. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL. 2. LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION. (WHEN FORMED PARALLEL).</p> | MILLIMETERS | | INCHES | | DIM | MIN MAX | MIN | MAX | A | 31.24 32.77 | 1.230 | 1.290 | B | 12.70 15.49 | 0.500 | 0.610 | C | 4.06 5.59 | 0.160 | 0.220 | D | 0.41 0.51 | 0.016 | 0.020 | F | 1.77 1.92 | 0.050 | 0.060 | G | 2.54 BSC | 0.100 BSC | | J | 0.20 0.30 | 0.008 | 0.012 | K | 3.18 4.06 | 0.125 | 0.160 | L | 15.24 BSC | 0.600 BSC | | M | 0° 15° | 0° 15° | | N | 0.51 1.27 | 0.020 | 0.050 |
|--|-------------|-----------|--------|--|-----|---------|-----|-----|---|-------------|-------|-------|---|-----------|-------|-------|---|-----------|-------|-------|---|-----------|-------|-------|---|-----------|-------|-------|---|----------|-----------|--|---|-----------|-------|-------|---|-----------|-------|-------|---|-----------|-------|-------|---|-----------|-----------|-------|---|-------|-------|--|---|-----------|-------|-------|--|-------------|--|--------|--|-----|---------|-----|-----|---|-------------|-------|-------|---|-------------|-------|-------|---|-----------|-------|-------|---|-----------|-------|-------|---|-----------|-------|-------|---|----------|-----------|--|---|-----------|-------|-------|---|-----------|-------|-------|---|-----------|-----------|--|---|--------|--------|--|---|-----------|-------|-------|
| MILLIMETERS | | INCHES | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DIM | MIN MAX | MIN | MAX | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | 19.95 19.81 | 0.790 | 0.790 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | 6.32 6.30 | 0.248 | 0.275 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | 4.06 5.00 | 0.160 | 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | 0.38 0.51 | 0.015 | 0.020 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| F | 1.40 1.65 | 0.055 | 0.065 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| G | 2.54 BSC | 0.100 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| H | 0.51 1.14 | 0.020 | 0.045 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| J | 0.20 0.30 | 0.008 | 0.012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| K | 3.18 4.06 | 0.125 | 0.160 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| L | 2.27 2.27 | 0.290 | 0.310 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M | — 15° | — 15° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| N | 0.51 1.02 | 0.020 | 0.040 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MILLIMETERS | | INCHES | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DIM | MIN MAX | MIN | MAX | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | 31.24 32.77 | 1.230 | 1.290 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | 12.70 15.49 | 0.500 | 0.610 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | 4.06 5.59 | 0.160 | 0.220 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | 0.41 0.51 | 0.016 | 0.020 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| F | 1.77 1.92 | 0.050 | 0.060 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| G | 2.54 BSC | 0.100 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| J | 0.20 0.30 | 0.008 | 0.012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| K | 3.18 4.06 | 0.125 | 0.160 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| L | 15.24 BSC | 0.600 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M | 0° 15° | 0° 15° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| N | 0.51 1.27 | 0.020 | 0.050 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>P SUFFIX PLASTIC PACKAGE CASE 626-04</p> <table border="1"> <thead> <tr> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>DIM</th> <th>MIN MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr><td>A</td><td>9.40 10.16</td><td>0.370</td><td>0.400</td></tr> <tr><td>B</td><td>6.10 6.60</td><td>0.240</td><td>0.260</td></tr> <tr><td>C</td><td>3.94 4.45</td><td>0.155</td><td>0.175</td></tr> <tr><td>D</td><td>0.38 0.51</td><td>0.015</td><td>0.020</td></tr> <tr><td>F</td><td>1.02 1.52</td><td>0.040</td><td>0.060</td></tr> <tr><td>G</td><td>2.54 BSC</td><td>0.100 BSC</td><td></td></tr> <tr><td>H</td><td>0.76 1.27</td><td>0.030</td><td>0.050</td></tr> <tr><td>J</td><td>0.20 0.30</td><td>0.008</td><td>0.012</td></tr> <tr><td>K</td><td>2.92 3.43</td><td>0.115</td><td>0.135</td></tr> <tr><td>L</td><td>7.62 BSC</td><td>0.300 BSC</td><td></td></tr> <tr><td>M</td><td>— 10°</td><td>— 10°</td><td></td></tr> <tr><td>N</td><td>0.51 0.76</td><td>0.020</td><td>0.030</td></tr> </tbody> </table> <p>NOTES: 1. LEAD POSITIONAL TOLERANCE: $\phi 0.13 (0.005) \text{ T A } \textcircled{B}$ 2. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL. 3. PACKAGE CONTOUR OPTIONAL (ROUND OR SQUARE CORNERS). 4. DIMENSIONS A AND B ARE DATUMS. 5. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.</p> | MILLIMETERS | | INCHES | | DIM | MIN MAX | MIN | MAX | A | 9.40 10.16 | 0.370 | 0.400 | B | 6.10 6.60 | 0.240 | 0.260 | C | 3.94 4.45 | 0.155 | 0.175 | D | 0.38 0.51 | 0.015 | 0.020 | F | 1.02 1.52 | 0.040 | 0.060 | G | 2.54 BSC | 0.100 BSC | | H | 0.76 1.27 | 0.030 | 0.050 | J | 0.20 0.30 | 0.008 | 0.012 | K | 2.92 3.43 | 0.115 | 0.135 | L | 7.62 BSC | 0.300 BSC | | M | — 10° | — 10° | | N | 0.51 0.76 | 0.020 | 0.030 | <p>L SUFFIX CERAMIC PACKAGE CASE 632-08</p> <table border="1"> <thead> <tr> <th colspan="2">MILLIMETERS</th> <th colspan="2">INCHES</th> </tr> <tr> <th>DIM</th> <th>MIN MAX</th> <th>MIN</th> <th>MAX</th> </tr> </thead> <tbody> <tr><td>A</td><td>19.05 19.94</td><td>0.750</td><td>0.785</td></tr> <tr><td>B</td><td>6.23 7.11</td><td>0.245</td><td>0.280</td></tr> <tr><td>C</td><td>3.94 5.08</td><td>0.155</td><td>0.200</td></tr> <tr><td>D</td><td>0.38 0.50</td><td>0.015</td><td>0.020</td></tr> <tr><td>F</td><td>1.40 1.65</td><td>0.055</td><td>0.065</td></tr> <tr><td>G</td><td>2.54 BSC</td><td>0.100 BSC</td><td></td></tr> <tr><td>J</td><td>0.21 0.38</td><td>0.008</td><td>0.015</td></tr> <tr><td>K</td><td>3.18 4.31</td><td>0.125</td><td>0.170</td></tr> <tr><td>L</td><td>7.62 BSC</td><td>0.300 BSC</td><td></td></tr> <tr><td>M</td><td>0° 15°</td><td>0° 15°</td><td></td></tr> <tr><td>N</td><td>0.51 1.01</td><td>0.020</td><td>0.040</td></tr> </tbody> </table> <p>NOTES: 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982. 2. CONTROLLING DIMENSION: INCH. 3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL. 4. DIM F MAY NARROW TO 0.76 (0.030) WHERE THE LEAD ENTERS THE CERAMIC BODY.</p> | MILLIMETERS | | INCHES | | DIM | MIN MAX | MIN | MAX | A | 19.05 19.94 | 0.750 | 0.785 | B | 6.23 7.11 | 0.245 | 0.280 | C | 3.94 5.08 | 0.155 | 0.200 | D | 0.38 0.50 | 0.015 | 0.020 | F | 1.40 1.65 | 0.055 | 0.065 | G | 2.54 BSC | 0.100 BSC | | J | 0.21 0.38 | 0.008 | 0.015 | K | 3.18 4.31 | 0.125 | 0.170 | L | 7.62 BSC | 0.300 BSC | | M | 0° 15° | 0° 15° | | N | 0.51 1.01 | 0.020 | 0.040 |
| MILLIMETERS | | INCHES | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DIM | MIN MAX | MIN | MAX | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | 9.40 10.16 | 0.370 | 0.400 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | 6.10 6.60 | 0.240 | 0.260 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | 3.94 4.45 | 0.155 | 0.175 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | 0.38 0.51 | 0.015 | 0.020 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| F | 1.02 1.52 | 0.040 | 0.060 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| G | 2.54 BSC | 0.100 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| H | 0.76 1.27 | 0.030 | 0.050 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| J | 0.20 0.30 | 0.008 | 0.012 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| K | 2.92 3.43 | 0.115 | 0.135 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| L | 7.62 BSC | 0.300 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M | — 10° | — 10° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| N | 0.51 0.76 | 0.020 | 0.030 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MILLIMETERS | | INCHES | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DIM | MIN MAX | MIN | MAX | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A | 19.05 19.94 | 0.750 | 0.785 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B | 6.23 7.11 | 0.245 | 0.280 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| C | 3.94 5.08 | 0.155 | 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| D | 0.38 0.50 | 0.015 | 0.020 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| F | 1.40 1.65 | 0.055 | 0.065 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| G | 2.54 BSC | 0.100 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| J | 0.21 0.38 | 0.008 | 0.015 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| K | 3.18 4.31 | 0.125 | 0.170 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| L | 7.62 BSC | 0.300 BSC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M | 0° 15° | 0° 15° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| N | 0.51 1.01 | 0.020 | 0.040 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

PACKAGE OUTLINE DIMENSIONS (continued)

T-90-20


P SUFFIX
PLASTIC PACKAGE
CASE 646-06



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 18.16 | 19.56 | 0.715 | 0.770 |
| B | 6.10 | 6.60 | 0.240 | 0.260 |
| C | 3.69 | 4.69 | 0.145 | 0.185 |
| D | 0.38 | 0.53 | 0.015 | 0.021 |
| F | 1.02 | 1.78 | 0.040 | 0.070 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 1.32 | 2.41 | 0.052 | 0.095 |
| J | 0.20 | 0.38 | 0.008 | 0.015 |
| K | 2.92 | 3.43 | 0.115 | 0.135 |
| L | 7.62 BSC | | 0.300 BSC | |
| M | 0° | 10° | 0° | 10° |
| N | 0.29 | 1.01 | 0.015 | 0.039 |

- NOTES:
- LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
 - DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 - DIMENSION "B" DOES NOT INCLUDE MOLD FLASH.
 - ROUNDED CORNERS OPTIONAL.

P SUFFIX
PLASTIC PACKAGE
CASE 648-08




| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 18.80 | 19.55 | 0.740 | 0.770 |
| B | 6.35 | 6.85 | 0.250 | 0.270 |
| C | 3.69 | 4.44 | 0.145 | 0.175 |
| D | 0.39 | 0.53 | 0.015 | 0.021 |
| F | 1.02 | 1.77 | 0.040 | 0.070 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 1.27 BSC | | 0.100 BSC | |
| J | 0.21 | 0.38 | 0.008 | 0.015 |
| K | 2.80 | 3.30 | 0.110 | 0.130 |
| L | 7.50 | 7.74 | 0.295 | 0.305 |
| M | 0° | 10° | 0° | 10° |
| S | 0.51 | 1.01 | 0.020 | 0.040 |

- NOTES:
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 - CONTROLLING DIMENSION: INCH.
 - DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 - DIMENSION "B" DOES NOT INCLUDE MOLD FLASH.
 - ROUNDED CORNERS OPTIONAL.

P SUFFIX
PLASTIC PACKAGE
CASE 649-03


(PW SUFFIX
FOR MC10H181
ONLY)



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 31.50 | 32.13 | 1.240 | 1.265 |
| B | 13.21 | 13.72 | 0.520 | 0.540 |
| C | 4.70 | 5.21 | 0.185 | 0.205 |
| D | 0.38 | 0.51 | 0.015 | 0.020 |
| F | 1.02 | 1.52 | 0.040 | 0.060 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 1.65 | 2.16 | 0.065 | 0.085 |
| J | 0.20 | 0.30 | 0.008 | 0.012 |
| K | 2.92 | 3.43 | 0.115 | 0.135 |
| L | 14.99 | 15.49 | 0.590 | 0.610 |
| M | 10° | | 10° | |
| N | 0.51 | 1.02 | 0.020 | 0.040 |
| P | 0.13 | 0.38 | 0.005 | 0.015 |
| Q | 0.51 | 0.76 | 0.020 | 0.030 |

- NOTES:
- LEADS WITHIN 0.13 mm (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
 - DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.


F SUFFIX
CERAMIC PACKAGE
CASE 650-05



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 9.40 | 9.90 | 0.370 | 0.390 |
| B | 6.73 | 6.80 | 0.265 | 0.269 |
| C | 1.53 | 2.15 | 0.060 | 0.085 |
| D | 0.38 | 0.48 | 0.014 | 0.019 |
| G | 1.27 BSC | | 0.050 BSC | |
| H | 0.64 | 0.01 | 0.025 | 0.040 |
| J | 0.11 | 0.17 | 0.004 | 0.007 |
| K | 6.35 | 9.39 | 0.250 | 0.370 |
| L | 18.93 | — | 0.745 | — |
| N | — | 0.50 | — | 0.020 |

- NOTES:
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 - CONTROLLING DIMENSION: INCH.
 - DIMENSION "A" AND "B" ALLOW FOR LID MISMATCH, AND GLASS MENISCUS.
 - DIMENSION "H" SHALL BE MEASURED AT THE POINT OF EXIT OF THE LEAD FROM THE BODY.
 - LEAD NUMBER 1 IDENTIFIED BY TAB ON LEAD OR DOT ON COVER.
 - DIMENSION "J" INCLUDES SOLDER LEAD FINISH.
 - LEAD NUMBERS SHOWN FOR REFERENCE ONLY.


**L SUFFIX
CERAMIC PACKAGE
CASE 693-02**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 9.91 | 10.92 | 0.390 | 0.430 |
| B | 6.22 | 6.99 | 0.245 | 0.275 |
| C | 4.32 | 5.08 | 0.170 | 0.200 |
| D | 0.41 | 0.51 | 0.016 | 0.020 |
| F | 1.40 | 1.65 | 0.055 | 0.065 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 1.14 | 1.65 | 0.045 | 0.065 |
| J | 0.20 | 0.30 | 0.008 | 0.012 |
| K | 3.18 | 4.08 | 0.125 | 0.160 |
| L | 7.37 | 7.87 | 0.290 | 0.310 |
| M | — | 15° | — | 15° |
| N | 0.51 | 1.02 | 0.020 | 0.040 |

- NOTES:
 1. LEADS WITHIN 0.13 mm (0.005) RAD OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
 2. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.


**P SUFFIX
PLASTIC PACKAGE
CASE 707-02**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 22.27 | 23.24 | 0.875 | 0.915 |
| B | 6.10 | 6.60 | 0.240 | 0.260 |
| C | 3.56 | 4.57 | 0.140 | 0.180 |
| D | 0.36 | 0.56 | 0.014 | 0.022 |
| F | 1.27 | 1.78 | 0.050 | 0.070 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 1.02 | 1.52 | 0.040 | 0.060 |
| J | 0.20 | 0.30 | 0.008 | 0.012 |
| K | 2.92 | 3.43 | 0.115 | 0.135 |
| L | 7.62 BSC | | 0.300 BSC | |
| M | 0° | 15° | 0° | 15° |
| N | 0.51 | 1.02 | 0.020 | 0.040 |

- NOTES:
 1. POSITIONAL TOLERANCE OF LEADS (D), SHALL BE WITHIN 0.25mm(0.010) AT MAXIMUM MATERIAL CONDITION, IN RELATION TO SEATING PLANE AND EACH OTHER.
 2. DIMENSION "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 3. DIMENSION B DOES NOT INCLUDE MOLD FLASH.


**P SUFFIX
PLASTIC PACKAGE
CASE 724-03**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 31.25 | 32.13 | 1.230 | 1.265 |
| B | 6.35 | 6.85 | 0.250 | 0.270 |
| C | 3.68 | 4.44 | 0.145 | 0.175 |
| D | 0.38 | 0.51 | 0.015 | 0.020 |
| E | 1.27 BSC | | 0.050 BSC | |
| F | 1.02 | 1.52 | 0.040 | 0.060 |
| G | 2.54 BSC | | 0.100 BSC | |
| J | 0.18 | 0.30 | 0.007 | 0.012 |
| K | 2.80 | 3.56 | 0.110 | 0.140 |
| L | 7.62 BSC | | 0.300 BSC | |
| M | 0° | 15° | 0° | 15° |
| N | 0.51 | 1.01 | 0.020 | 0.040 |

- NOTES:
 1. CHAMFERED CONTOUR OPTIONAL.
 2. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 3. DIMENSIONS AND TOLERANCES PER ANSI Y14.34, 1982.
 4. CONTROLLING DIMENSION: INCH.

**L SUFFIX
CERAMIC PACKAGE
CASE 726-04**




| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 22.35 | 23.11 | 0.880 | 0.910 |
| B | 6.10 | 7.49 | 0.240 | 0.295 |
| C | — | 5.08 | — | 0.200 |
| D | 0.38 | 0.53 | 0.015 | 0.021 |
| F | 1.40 | 1.78 | 0.055 | 0.070 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 0.51 | 1.14 | 0.020 | 0.045 |
| J | 0.20 | 0.30 | 0.008 | 0.012 |
| K | 3.18 | 4.32 | 0.125 | 0.170 |
| L | 7.62 BSC | | 0.300 BSC | |
| M | 0° | 15° | 0° | 15° |
| N | 0.51 | 1.02 | 0.020 | 0.040 |

- NOTES:
 1. LEADS, TRUE POSITIONED WITHIN 0.25 mm (0.010) DIA. AT SEATING PLANE, AT MAXIMUM MATERIAL CONDITION.
 2. DIM "L" TO CENTER OF LEADS WHEN FORMED PARALLEL.
 3. DIM "A" & "B" INCLUDES MENISCUS.
 4. "F" DIMENSION IS FOR FULL LEADS. "HALF" LEADS ARE OPTIONAL AT LEAD POSITIONS 1, 9, 10, AND 18.

PACKAGE OUTLINE DIMENSIONS (continued)

1


**L SUFFIX
CERAMIC PACKAGE
CASE 732-03**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 23.88 | 25.15 | 0.940 | 0.990 |
| B | 6.80 | 7.49 | 0.260 | 0.295 |
| C | 3.81 | 5.08 | 0.150 | 0.200 |
| D | 0.38 | 0.56 | 0.015 | 0.022 |
| F | 1.40 | 1.65 | 0.055 | 0.065 |
| G | 2.54 BSC | | 0.100 BSC | |
| H | 0.51 | 1.27 | 0.020 | 0.050 |
| J | 0.20 | 0.30 | 0.008 | 0.012 |
| K | 3.18 | 4.06 | 0.125 | 0.160 |
| L | 7.62 BSC | | 0.300 BSC | |
| M | 0° | 15° | 0° | 15° |
| N | 0.25 | 1.02 | 0.010 | 0.040 |

- NOTES:
 1. LEADS WITHIN 0.25 mm (0.010) DIA., TRUE POSITION AT SEATING PLANE, AT MAXIMUM MATERIAL CONDITION.
 2. DIM L TO CENTER OF LEADS WHEN FORMED PARALLEL.
 3. DIM A AND B INCLUDES MENISCUS.


**P SUFFIX
PLASTIC PACKAGE
CASE 738-03**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 25.55 | 27.17 | 1.010 | 1.070 |
| B | 6.10 | 6.60 | 0.240 | 0.260 |
| C | 3.81 | 4.57 | 0.150 | 0.180 |
| D | 0.38 | 0.56 | 0.015 | 0.022 |
| E | 1.27 BSC | | 0.050 BSC | |
| F | 1.27 | 1.77 | 0.050 | 0.070 |
| G | 2.54 BSC | | 0.100 BSC | |
| J | 0.21 | 0.38 | 0.008 | 0.015 |
| K | 2.80 | 3.55 | 0.110 | 0.140 |
| L | 7.62 BSC | | 0.300 BSC | |
| M | 0° | 15° | 0° | 15° |
| N | 0.51 | 1.01 | 0.020 | 0.040 |

- NOTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. DIMENSION "L" TO CENTER OF LEAD WHEN FORMED PARALLEL.
 4. DIMENSION "B" DOES NOT INCLUDE MOLD FLASH.


**D SUFFIX
PLASTIC SOIC PACKAGE
CASE 751-03**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.80 | 5.00 | 0.189 | 0.196 |
| B | 3.90 | 4.00 | 0.150 | 0.157 |
| C | 1.35 | 1.75 | 0.054 | 0.068 |
| D | 0.35 | 0.49 | 0.014 | 0.019 |
| F | 0.40 | 1.25 | 0.015 | 0.049 |
| G | 0.27 BSC | | 0.050 BSC | |
| J | 0.18 | 0.25 | 0.007 | 0.009 |
| K | 0.10 | 0.25 | 0.004 | 0.009 |
| M | 0° | 7° | 0° | 7° |
| P | 5.80 | 6.20 | 0.229 | 0.244 |
| R | 0.25 | 0.50 | 0.010 | 0.019 |

- NOTES:
 1. DIMENSIONS "A" AND "B" ARE DATUMS AND "T" IS A DATUM SURFACE.
 2. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 3. CONTROLLING DIM: MILLIMETER.
 4. DIMENSION "A" AND "B" DO NOT INCLUDE MOLD PROTRUSION.
 5. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.

**L SUFFIX
CERAMIC PACKAGE
CASE 758-01**



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 31.50 | 32.64 | 1.240 | 1.285 |
| B | 7.24 | 7.75 | 0.285 | 0.305 |
| C | 3.68 | 4.44 | 0.145 | 0.175 |
| D | 0.38 | 0.53 | 0.015 | 0.021 |
| F | 1.14 | 1.97 | 0.045 | 0.062 |
| G | 2.54 BSC | | 0.100 BSC | |
| J | 0.20 | 0.33 | 0.008 | 0.013 |
| K | 2.54 | 4.19 | 0.100 | 0.165 |
| L | 7.62 | 7.87 | 0.300 | 0.310 |
| N | 0.51 | 1.27 | 0.020 | 0.050 |
| P | 9.14 | 10.16 | 0.360 | 0.400 |

- NOTES:
 1. DIMENSION A IS DATUM.
 2. POSITIONAL TOLERANCE FOR LEADS: 24 PLACES $\pm 0.25 (0.010) \text{ } \textcircled{T} \text{ } \textcircled{A} \text{ } \textcircled{B}$
 3. [T] IS SEATING PLANE.
 4. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
 5. DIMENSIONING AND TOLERANCING PER ANSI Y14.5, 1973.

1

**FN SUFFIX
PLASTIC PACKAGE
CASE 775-02**

NOTES:

- DATUMS -L-, -M-, -N-, AND -P- DETERMINED WHERE TOP OF LEAD SHOULDER EXIT PLASTIC BODY AT MOLD PARTING LINE.
- DIM G1, TRUE POSITION TO BE MEASURED AT DATUM -T-, SEATING PLANE.
- DIM R AND U DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.25 (0.010) PER SIDE.
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: INCH.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 9.78 | 10.03 | 0.385 | 0.395 |
| B | 9.78 | 10.03 | 0.385 | 0.395 |
| C | 4.20 | 4.57 | 0.165 | 0.180 |
| E | 2.29 | 2.79 | 0.090 | 0.110 |
| F | 0.33 | 0.48 | 0.013 | 0.019 |
| G | 1.27 BSC | | 0.050 BSC | |
| H | 0.66 | 0.81 | 0.026 | 0.032 |
| J | 0.51 | — | 0.020 | — |
| K | 0.64 | — | 0.025 | — |
| R | 8.89 | 9.04 | 0.350 | 0.356 |
| U | 8.89 | 9.04 | 0.350 | 0.356 |
| V | 1.07 | 1.21 | 0.042 | 0.048 |
| W | 1.07 | 1.21 | 0.042 | 0.048 |
| X | 1.07 | 1.42 | 0.042 | 0.056 |
| Y | — | 0.50 | — | 0.020 |
| Z | 2° | 10° | 2° | 10° |
| G1 | 7.88 | 8.38 | 0.310 | 0.330 |
| K1 | 1.02 | — | 0.040 | — |
| Z1 | 2° | 10° | 2° | 10° |

**FN SUFFIX
PLASTIC PACKAGE
CASE 776-02**

NOTES:

- DUE TO SPACE LIMITATION, CASE 776-02 SHALL BE REPRESENTED BY A GENERAL (SMALLER) CASE OUTLINE DRAWING RATHER THAN SHOWING ALL 28 LEADS.
- DATUMS -L-, -M-, -N-, AND -P- DETERMINED WHERE TOP OF LEAD SHOULDER EXIT PLASTIC BODY AT MOLD PARTING LINE.
- DIM G1, TRUE POSITION TO BE MEASURED AT DATUM -T-, SEATING PLANE.
- DIM R AND U DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION IS 0.25 (0.010) PER SIDE.
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: INCH.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 12.32 | 12.57 | 0.485 | 0.495 |
| B | 12.32 | 12.57 | 0.485 | 0.495 |
| C | 4.20 | 4.57 | 0.165 | 0.180 |
| E | 2.29 | 2.79 | 0.090 | 0.110 |
| F | 0.33 | 0.48 | 0.013 | 0.019 |
| G | 1.27 BSC | | 0.050 BSC | |
| H | 0.66 | 0.81 | 0.026 | 0.032 |
| J | 0.51 | — | 0.020 | — |
| K | 0.64 | — | 0.025 | — |
| R | 11.43 | 11.58 | 0.450 | 0.456 |
| U | 11.43 | 11.58 | 0.450 | 0.456 |
| V | 1.07 | 1.21 | 0.042 | 0.048 |
| W | 1.07 | 1.21 | 0.042 | 0.048 |
| X | 1.07 | 1.42 | 0.042 | 0.056 |
| Y | — | 0.50 | — | 0.020 |
| Z | 2° | 10° | 2° | 10° |
| G1 | 10.42 | 10.92 | 0.410 | 0.430 |
| K1 | 1.02 | — | 0.040 | — |
| Z1 | 2° | 10° | 2° | 10° |

MECL Logic Surface Mount

WHY SURFACE MOUNT?

Surface Mount Technology is now being utilized to offer answers to many problems that have been created in the use of insertion technology.

Limitations have been reached with insertion packages and PC board technology. Surface Mount Technology offers the opportunity to continue to advance the State-of-the-Art designs that cannot be accomplished with Insertion Technology.

Surface Mount Packages allow more optimum device performance with the smaller Surface Mount configuration. Internal lead lengths, parasitic capacitance and inductance that placed limitations on chip performance have been reduced.

The lower profile of Surface Mount Packages allows more boards to be utilized in a given amount of space. They are stacked closer together and utilize less total volume than insertion populated PC boards.

Printed circuit costs are lowered with the reduction of the number of board layers required. The elimination or reduction of the number of plated through holes in the board, contribute significantly to lower PC board prices.

Surface Mount assembly does not require the preparation of components that are common on insertion technology lines. Surface Mount components are sent directly to the assembly line, eliminating an intermediate step.

Automatic placement equipment is available that can place Surface Mount components at the rate of a few thousand per hour to hundreds of thousands of components per hour.

Surface Mount Technology is cost effective, allowing the manufacturer the opportunity to produce smaller units and offer increased functions with the same size product.

MECL AVAILABILITY IN SURFACE MOUNT

Motorola is now offering MECL 10K and MECL 10KH in the PLCC (Plastic Leaded Chip Carrier) packages.

MECL in PLCC may be ordered in conventional plastic rails or on Tape and Reel. Refer to the Tape and Reel section for ordering details.

TAPE AND REEL


Motorola has now added the convenience of Tape and Reel packaging for our growing family of standard Integrated Circuit products. The packaging fully conforms to

the latest EIA RS-481A specification. The antistatic embossed tape provides a secure cavity sealed with a peel-back cover tape.

GENERAL INFORMATION

- Reel Size 13 inch (330 mm) Suffix: R2
- Tape Width 16 mm
- Units/Reel 1000

MECHANICAL POLARIZATION



ORDERING INFORMATION

- Minimum Lot Size/Device Type = 3000 Pieces.
- No Partial Reel Counts Available.
- To order devices which are to be delivered in Tape and Reel, add the appropriate suffix to the device number being ordered.

EXAMPLE:

ORDERING CODE

- MC10100FN
- MC10100FNR2
- MC10H100FN
- MC10H100FNR2
- MC12015D
- MC12015DR2

SHIPMENT METHOD

- Magazines (Rails)
- 13 inch Tape and Reel
- Magazines (Rails)
- 13 inch Tape and Reel
- Magazines (Rails)
- 13 inch Tape and Reel

DUAL-IN-LINE PACKAGE TO PLCC PIN CONVERSION DATA

The following tables give the equivalent I/O pinouts of Dual-In-Line (DIL) packages and Plastic Leaded Chip Carrier (PLCC) packages.

Conversion Tables

| | | | | | | | | | | | | | | | | |
|-------------|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|
| 16 PIN DIL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
| 20 PIN PLCC | 2 | 3 | 4 | 5 | 7 | 8 | 9 | 10 | 12 | 13 | 14 | 15 | 17 | 18 | 19 | 20 |

| | | | | | | | | | | | | | | | | | | | | |
|-------------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|
| 20 PIN DIL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| 20 PIN PLCC | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |

| | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| 24 PIN DIL | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 |
| 28 PIN PLCC | 2 | 3 | 4 | 5 | 6 | 7 | 9 | 10 | 11 | 12 | 13 | 14 | 16 | 17 | 18 | 19 | 20 | 21 | 23 | 24 | 25 | 26 | 27 | 28 |