


FRD Type :10ELS2

OUTLINE DRAWING

FEATURES

- * Miniature Size
- * Fast Recovery and Low Price
- * High Surge Capability
- * 100volts trough 600volts Types Available
- * 26mm and 52mm Inside Tape Spacing



Maximum Ratings

Approx Net Weight:0.17g

Rating		Symbol	10ELS2			Unit
Repetitive Peak Reverse Voltage		V_{RRM}	200			V
Non-repetitive Peak Reverse Voltage		V_{RSM}	400			V
Average Rectified Output Current	P.C.Board Mounted *	I_O	1	$T_a=26^{\circ}C$	Half Sine Wave Resistive Load	A
RMS Forward Current		$I_{F(RMS)}$	1.57			A
Surge Forward Current		I_{FSM}	30	Half Sine Wave,1cycle,Non-repetitive		A
Operating JunctionTemperature Range		T_{jw}	- 40 to + 150			$^{\circ}C$
Storage Temperature Range		T_{stg}	- 40 to + 150			$^{\circ}C$

Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min	Typ	Max	Unit
Peak Reverse Current	I_{RM}	$T_j= 25^{\circ}C, V_{RM}= V_{RRM}$	-	-	10	μA
Peak Forward Voltage	V_{FM}	$T_j= 25^{\circ}C, I_{FM}= 1 A$	-	-	1.1	V
Reverse Recovery Time	t_{rr}	$I_{FM}= 1 A, -di/dt= 50 A/\mu s, T_a= 25^{\circ}C$	-	-	150	ns
Thermal Resistance	$R_{th(j-a)}$	Without Fin or P.C.Board*	-	-	100	$^{\circ}C/W$

*:L=3mm, Print Lands = 7x7 mm,Both Sides

10ELS2 OUTLINE DRAWING (Dimensions in mm)

