


Bulk Metal® Foil Technology

Precision Trimming Potentiometers, QPL Approved 1/4 Inch Square, Qualified to MIL-PRF-22097, Char. F, RJ26



FEATURES

- Temperature coefficient of resistance (TCR): ± 10 ppm/°C maximum⁴⁾ (- 55 °C to + 150 °C ref. at + 25 °C); through the wiper⁵⁾; ± 25 ppm/°C
- Load life stability: 0.1 % typical ΔR , 1.0 % maximum ΔR under full rated power of 0.25 W at 85 °C for 1000 h
- Settability: 0.05 % typical; 0.1 % maximum
- Setting stability: 0.1 % typical; 0.5 % maximum, ΔSS
- Power rating: 0.25 W at + 85 °C
- Resistance range: 50 Ω to 5 k Ω
- Resistance tolerance: ± 10 %
- Terminal finish: gold plated

www.DataSheet4U.com

TABLE 1 - MODEL SELECTION*						
MODEL	TERMINATION STYLE	AVERAGE WEIGHT (g)	STANDARD RESISTANCE VALUES (in Ω) ¹⁾	STANDARD TOLERANCE ²⁾	POWER RATING at + 85 °C AMBIENT	NO. OF TURNS
1242 (RJ26)	W-edge mount, top adjust	0.4	50, 100, 200, 500, 1K, 2K, 5K	± 10 %	0.25 W	21 \pm 2
	X-edge mount, side adjust					

Note

* See figure 1

TABLE 2 - 1242 (RJ26) SERIES ELECTRICAL SPECIFICATIONS ³⁾	
Temperature Coefficient of Resistance (TCR) End-to-end ⁴⁾ Through the wiper ⁵⁾	± 10 ppm/°C maximum (- 55 °C to + 150 °C, 25 °C ref.) ± 25 ppm/°C
Stability Load life at 1000 h	0.1 % typical ΔR 1.0 % maximum ΔR (under full rated power of 0.25 W at + 85 °C)
Power Rating (at + 85 °C) ⁶⁾	0.25 W
Settability	0.05 % typical; 0.1 % maximum
Setting Stability	0.1 % typical; 0.5 % maximum ΔSS
Contact Resistance Variation - CRV (noise)	± 3 % or 3 Ω ⁷⁾
Hop-off	0.25 % typical; 1.0 % maximum
High-Frequency Operation Rise time Inductance Capacitance	1.0 ns without ringing 0.08 μH typical 0.5 pF typical
Operating Temperature Range	- 55 °C to + 150 °C



Note

• See page 3 for footnotes

TABLE 3 - MECHANICAL SPECIFICATIONS	
Adjustment Turns	21 \pm 2
Mechanical Stops	Wiper idles - no discontinuity
Internal Terminations	All welded - no flux
Case Material	Diallyl-phthalate: green (DAP)
Shaft Torque	3 oz. in. maximum
Backlash	0.005 % typical

FIGURE 1 - SCHEMATIC AND DIMENSIONS in inches (millimeters)

1242W



STANDARD MARKING:



- Model No.
- Date Code
- Resistance Value
- Tolerance

NOTES:

Adjustment screw 0.070" (1.78 mm) diameter with 0.020" (0.51 mm) X 0.020" (0.51 mm) slot. Model 1242 has gold plated terminal pins 0.016" (0.41 mm) ± 0.001" (0.03 mm) diameter, 0.200" (5.08 mm) length minimum.

TOLERANCES:

- A = ± 0.005" (0.13)
- C = ± 0.010" (0.25)
- D = ± 0.020" (0.51)



1242X








FIGURE 2 - POWER DERATING CURVE





Bulk Metal® Foil Technology
 Precision Trimming Potentiometers, QPL Approved 1/4 Inch
 Square, Qualified to MIL-PRF-22097, Char. F, RJ26

Vishay Foil Resistors


TABLE 4 - COMPARISON		
	MIL-PRF-22097/5 CHARACTERISTIC F ⁸⁾	(RJ26) 1242 SPECIFICATIONS
TEST GROUP I		
Visual and mechanical	No failures	No failures
Total resistance	± 10 %	± 10 %
Actual effective electrical travel	10 to 25 turns	21 ± 2 turns
End resistance	± 2 % or 20 Ω ⁷⁾	2 Ω (values ≤ 1 kΩ) ; 5 Ω (values ≥ 2 kΩ)
Contact resistance variation - CRV (noise)	± 3.0 % or 3 Ω ⁷⁾	± 3.0 % or 3 Ω ⁷⁾
Dielectric withstanding voltage - DWV (atmospheric and barometric pressure)	Per MIL-STD-202, methods 301 and 105	Per MIL-STD-202, methods 301 and 105
Insulation resistance	> 1000 MΩ	> 1000 MΩ
Shaft torque	3 oz. in. maximum	3 oz. in. maximum
Thermal shock	± 1.0 %	0.1 % typical; 0.5 % maximum
TEST GROUP II		
Resistance temperature characteristic - TCR	± 0.01 % (± 100 ppm/°C)	± 0.001 % (10 ppm/°C)
Moisture resistance	± 1.0 %	± 0.5 %
Contact resistance variation - CRV (noise)	± 3.0 % or 3 Ω ⁷⁾	± 3.0 % or 3 Ω ⁷⁾
TEST GROUP III		
Shock (specified pulse)	± 1.0 %	± 0.5 %
Vibration (high-frequency)	± 1.0 %	± 0.5 %
Contact resistance variation - CRV (noise)	± 3.0 % or 3 Ω ⁷⁾	± 3.0 % or 3 Ω ⁷⁾
Salt spray	No corrosion	No corrosion
TEST GROUP IV		
Solder heat	± 1.0 %	± 0.1 %
Life (1000 h at 85 °C)	± 2.0 %	± 1.0 %
Contact resistance variation - CRV (noise)	± 3.0 % or 3 Ω ⁷⁾	± 3.0 % or 3 Ω ⁷⁾
TEST GROUP V		
Low-temperature operation	± 1.0 %	± 0.5 %
High-temperature exposure	± 2.0 %	± 0.5 %
Contact resistance variation - CRV (noise)	± 3.0 % or 3 Ω ⁷⁾	± 3.0 % or 3 Ω ⁷⁾
TEST GROUP VI		
Rotational life	± 2.0 %	± 2.0 %
Contact resistance variation - CRV (noise)	± 3.0 % or 3 Ω ⁷⁾	± 3.0 % or 3 Ω ⁷⁾
Terminal strength	2 lbs.	2 lbs.
TEST GROUP VII		
Solderability	MIL-STD-202 method 208	MIL-STD-202 method 208
Immersion	No continuous stream of bubbles	No continuous stream of bubbles
TEST GROUP VIII		
Fungus	MIL-STD-810 method 508	MIL-STD-810 method 508
	No mechanical damage	No mechanical damage

Notes

1. 5 Ω, 10 Ω, and 20 Ω resistance values available on special order.
2. 5 % resistance tolerance available on special order.
3. Maximum is 1.0 % A.Q.L. standard for all specifications except TCR. (For TCR information, see notes 4 and 5.) "Typical" is a designers reference which represents that 85 % of the lots supplied, over a long period of time, will be at least the figure shown or better.
4. Maximum TCR applies to the 3 σ (sigma) limit or 99.73 % of a production lot. (Measured end-to-end with wiper off the element.)
5. Measurements of TCR through the wiper are influenced more by setting stability and the percentage of the total/resistance in use (at the wiper) than by fundamental resistance change due to temperature alone. The parameter shown in table 2 is a 2 s distribution typifying the behavior of the device when used with 40 % or more of the total resistance in use.
6. Derated linearly for full power at + 85 °C to zero (0) W at + 150 °C. See figure 2 on previous page.
7. Whichever is greater.
8. All ΔR's are measured to the tolerance specified + 0.01 Ω.

TABLE 5 - GLOBAL PART NUMBER INFORMATION

NEW GLOBAL PART NUMBER: Y0057500R000K0L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y0057 500R000 K 0 L:

TYPE: 1242W
 VALUE: 500.0 Ω
 ABSOLUTE TOLERANCE: ± 10.0 %
 TERMINATION: gold plated
 PACKAGING: bulk pack

HISTORICAL PART NUMBER: RJ26 F W 501 (will continue to be used)

RJ26	F	W	501
MODEL	CHARACTERISTIC	MOUNTING TYPE	RESISTANCE VALUE
RJ26	Having specifications per table 1 of MIL-PRF-22097 (i.e., TCR of 100 ppm/°C, power rating of 0.25 W at + 85 °C and improved environmental specifications)	W, PC pins (edge mount, top adjust) X, PC pins (edge mount, side adjust)	First 2 digits significant, last digit represents the number of zeros (i.e., 501 = 500 Ω)

Note

* Application engineering release: for non-standard requests, please contact application engineering.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.