

- ◆Si APN
- ◆RoHS COMPLIANT

1. APPLICATION

Computer Switch Power Supply and
All kinds of power switch circuit

2. FEATURES

- Features of good high temperature
- High switching speed

3. PACKAGE


TO-220

4. Electrical Characteristics

4.1 Absolute Maximum Ratings

$T_{amb} = 25^{\circ}\text{C}$ unless specified

PARAMETER		SYMBOL	VALUE	UNIT
Collector-Base Voltage		V_{CBO}	500	V
Collector-Emitter Voltage		V_{CEO}	350	V
Emitter-Base Voltage		V_{EBO}	9	V
Collector Current		I_C	8	A
Power Dissipation	$T_a=25^{\circ}\text{C}$	P_{tot}	2	W
	$T_c=25^{\circ}\text{C}$		75	
Junction Temperature		T_j	150	$^{\circ}\text{C}$
Storage Temperature		T_{stg}	-55~150	$^{\circ}\text{C}$



1 Base(B) 2 Collector(C) 3 Emitter(E)

4.2 Electrical Parameter

$T_{amb} = 25^{\circ}\text{C}$ unless specified

PARAMETER	SYMBOL	TEST CONDITION	VALUE			UNIT
			MIN	TYP	MAX	
Collector-Base Voltage	BV_{CBO}	$I_C=1\text{mA}, I_E=0$	500			V
Collector-Emitter Voltage	BV_{CEO}	$I_C=1\text{mA}, I_B=0$	350			V
Emitter-Base Voltage	BV_{EBO}	$I_E=1\text{mA}, I_C=0$	9			V
Collector-Base Cutoff Current	I_{CBO}	$V_{CB}=500\text{V}, I_E=0$			10	μA
Collector-Emitter Cutoff Current	I_{CEO}	$V_{CE}=350\text{V}, I_B=0$			20	μA
Emitter-Base Cutoff Current	I_{EBO}	$V_{EB}=9\text{V}, I_C=0$			10	μA
DC Current Gain	h_{FE}^*	$V_{CE}=5\text{V}, I_C=1\text{mA}$	8			
		$V_{CE}=5\text{V}, I_C=2\text{A}$	20		35	
Collector-Emitter Saturation Voltage	$V_{CE\text{ sat}}^*$	$I_C=5\text{A}, I_B=2.5\text{A}$			0.6	V
Base-Emitter Saturation Voltage	$V_{BE\text{ sat}}^*$	$I_C=5\text{A}, I_B=2.5\text{A}$			1.2	V
Rising Time	t_r	$I_C=500\text{mA} (\text{UI}9600)$			0.9	μs
Falling Time	t_f			0.20	0.5	μs
Storage Time	t_s		3		6	μs
Typical Frequency	f_T	$V_{CE}=10\text{V}, I_C=0.5\text{A}, f=1\text{MHz}$	4			MHz

*: Pulse test $t_p \leq 300 \mu\text{s}, \delta \leq 2\%$

5. Characteristic Curve

Fig1 SOA (DC)




Fig2 Ptot - T




Fig3 Static Characteristic




Fig4 hFE-Ic




Fig5 VCESat-Ic





Fig6 VBESat-Ic



6. Package Dimentions(Unit: mm)

T0-220

