

●14D series

Model Number		Maximum Allowable Voltage		Varistor Voltage V 1.0mA (V)	Clamping Voltage (MAX.)		Maximum Peak current (8/20μs)		Maximum Energy (10/1000μs)		Rated Power W	Typical Capacitance (Reference) @1KHz (pf)	UL	CS	D'E	
							Standard (A)	High Surge	Standard (JOULE)	High Surge						
Standard	High Surge	AC (V)	DC (V)		VC (v)	IP (A)										
14D180L	J	11	14	18(15-21)	36	10	1000	2000	4.0	7.0	0.10	11100	*	*	*	
14D220K	J	14	18	22(20 -24)	43				5.0	8.0		9100	*	*	*	
14D270K	J	17	22	27(24 -30)	53				6.0	10		7400	*	*	*	
14D330K	J	20	26	33(30 -36)	65				7.5	12		6100	*	*	*	
14D390K	J	25	31	39(35 - 43)	77				8.6	13		5100	*	*	*	
14D470K	J	30	38	47(42 - 52)	93				10.0	17		4300	*	*	*	
14D560K	J	35	45	56(50 - 62)	110				11.0	20		3600	*	*	*	
14D680K	J	40	56	68(61 - 75)	135				14.0	24		2900	*	*	*	
14D820K	J	50	65	82(74 - 90)	135				22.0	27		2400	*	*	*	
14D101K	J	60	85	100(90 - 110)	165				28.0	33		2000	*	*	*	
14D121K	J	75	100	120(108 - 132)	200	32.0	40	2700	*	*	*					
14D151K	J	95	125	150(135 - 165)	250	40.0	53	1300	*	*	*					
14D181K	J	115	150	180(162 - 198)	300	50.0	60	1100	*	*	*					
14D201K	J	130	170	200(185 - 225)	340	57.0	70	1000	*	*	*					
14D221K	J	140	180	220(198 - 242)	360	60.0	78	900	*	*	*					
14D241K	J	150	200	240(216 - 264)	395	63.0	84	830	*	*	*					
14D271K	J	175	225	270(243 - 297)	455	70.0	99	740	*	*	*					
14D301K	J	190	250	300(270 - 330)	500	77.0	108	670	*	*	*					
14D331K	J	210	275	330(297 - 363)	550	85.0	115	610	*	*	*					
14D361K	J	230	300	360(324 - 396)	595	93.0	130	560	*	*	*					
14D391K	J	250	320	390(351 - 429)	650	100.0	140	510	*	*	*					
14D431K	J	275	350	430(387 - 473)	710	115.0	155	460	*	*	*					
14D471K	J	300	385	470(423 - 517)	775	125.0	175	430	*	*	*					
14D511K	J	320	415	510(459 - 561)	845	125.0	180	390	*	*	*					
14D561K	J	350	460	560(504 - 616)	925	125.0	185	360	*	*	*					
14D621K	J	385	505	620(558 - 682)	1025	125.0	190	320	*	*	*					
14D681K	J	420	560	680(612 - 748)	1120	130.0	200	290	*	*	*					
14D751K	J	460	615	750(675 - 825)	1240	143.0	210	270	*	*	*					
14D781K	J	485	640	780(702 - 858)	1290	148.0	220	260	*	*	*					
14D821K	J	510	670	820(738 - 902)	1355	157.0	235	240	*	*	*					
14D911K	J	550	745	910(819 - 1001)	1500	175.0	255	220	*	*	*					
14D102K	J	625	825	1000(900 - 1100)	1650	190.0	280	200	*	*	*					
14D112K	J	680	895	1100(990 - 1210)	1815	213.0	310	180	*	*	*					
14D122K	J	740	975	1200(1080-1320)	1980	228.0	310	165		*	*					
14D152K	J	900	1200	1500(1350-1650)	2475	266.0	420	130		*	*					
14D182K	J	1000	1465	1800(1620-1980)	2970	336.0	510	110		*	*					

OPERATING TEMPERATURE RANGE: - 40°C TO +85°C

STORAGE TEMPERATURE RANGE: - 40°C TO +125°C

● **14D series**

