

# isc N-Channel MOSFET Transistor

# 17N60

### • FEATURES

- Drain Current  $I_D = 17A @ T_C = 25^\circ C$
- Drain Source Voltage  
:  $V_{DSS} = 600V(\text{Min})$
- Static Drain-Source On-Resistance  
:  $R_{DS(on)} = 0.45 \Omega (\text{Max})$
- Fast Switching
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

### • APPLICATIONS



- Switch mode power supply.

### • ABSOLUTE MAXIMUM RATINGS( $T_a = 25^\circ C$ )

SYMBOL	PARAMETER	VALUE	UNIT
$V_{DSS}$	Drain-Source Voltage	600	V
$V_{GS}$	Gate-Source Voltage-Continuous	$\pm 30$	V
$I_D$	Drain Current-Continuous	17	A
$I_{DM}$	Drain Current-Single Pulsed	68	A
$P_D$	Total Dissipation @ $T_C = 25^\circ C$	250	W
$T_j$	Max. Operating Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature	-55~150	$^\circ C$

### • THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{thj-c}$	Thermal Resistance, Junction to Case	0.5	$^\circ C/W$



## isc N-Channel MOSFET Transistor

17N60

## • ELECTRICAL CHARACTERISTICS

 $T_C=25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYPE	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0; I_D=250\mu\text{A}$	600			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=5\text{V}; I_D=250\mu\text{A}$	2.0		4.0	V
$V_{SD}$	Diode Forward On-voltage	$I_S=17\text{A}; V_{GS}=0$			1.5	V
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10\text{V}; I_D=8.5\text{A}$			0.45	$\Omega$
$I_{GSS}$	Gate-Body Leakage Current	$V_{GS}=\pm 30\text{V}; V_{DS}=0$			$\pm 100$	nA
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=480\text{V}; V_{GS}=0$			200	$\mu\text{A}$
$C_{iss}$	Input Capacitance	$V_{DS}=25\text{V};$			4000	pF
$C_{rss}$	Reverse Transfer capacitance	$V_{GS}=0\text{V};$			500	
$C_{oss}$	Output Capacitance	$f_r=1\text{MHz}$			140	
$t_r$	Rise Time	$V_{GS}=10\text{V};$			110	ns
$t_{d(on)}$	Turn-on Delay Time	$I_D=8.5\text{A};$			90	
$t_f$	Fall Time	$V_{DD}=350\text{V};$			95	
$t_{d(off)}$	Turn-off Delay Time	$R_L=50\Omega$			200	

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.