



PIN NO. VS PHASE

A	A COM	\bar{A}	B	B COM	\bar{B}
RED	BLK	YEL	BLU	WHT	ORG
4	5	6	3	2	1

Model Specifications

Model Number	Step Angle	Drive Sequence	Rated Current/Wdg	Winding Resistance	Holding Torque	Inductance	Rotor Inertia	Detent Torque	Weight
	Degrees		Amps	Ohms	Nm (kg-cm)	mH	kg-cm ²	Nm (g-cm)	g
17PU-H203V	3.75°	UNIPOLAR	0.6	5.5	0.074 (0.75)	4.4	0.028	0.006 (60)	180
17PU-H233V	3.75°	BIPOLAR	0.6	5.5	0.079 (0.80)	7.9	0.028	0.006 (60)	180
17PU-H204V	3.75°	UNIPOLAR	0.8	3.0	0.074 (0.75)	2.1	0.028	0.006 (60)	180
17PU-H244V	3.75°	BIPOLAR	0.8	3.0	0.079 (0.80)	3.8	0.028	0.006 (60)	180
17PU-H008V	3.75°	UNIPOLAR	0.6	8.3	0.114 (1.15)	7.3	0.034	0.008 (80)	200
17PU-H034V	3.75°	BIPOLAR	0.6	8.3	0.142 (1.45)	12.3	0.034	0.008 (80)	200
17PU-H018V	3.75°	UNIPOLAR	1.0	3.0	0.114 (1.15)	2.5	0.034	0.008 (80)	200
17PU-H048V	3.75°	BIPOLAR	1.0	3.0	0.142 (1.45)	4.0	0.034	0.008 (80)	200
17PU-H502V	3.75°	UNIPOLAR	0.6	8.9	0.142 (1.45)	7.4	0.040	0.009 (90)	220
17PU-H503V	3.75°	BIPOLAR	0.6	8.9	0.172 (1.75)	13.5	0.040	0.009 (90)	220
17PU-H504V	3.75°	UNIPOLAR	1.0	3.2	0.142 (1.45)	3.5	0.040	0.009 (90)	220
17PU-H505V	3.75°	BIPOLAR	1.0	3.2	0.172 (1.75)	5.9	0.040	0.009 (90)	220
17PU-H302V	3.75°	UNIPOLAR	1.0	3.5	0.167 (1.7)	2.9	0.045	0.0098 (100)	250
17PU-H301V	3.75°	BIPOLAR	1.0	3.5	0.205 (2.1)	4.6	0.045	0.0098 (100)	250
17PU-H304V	3.75°	UNIPOLAR	1.4	1.8	0.167 (1.7)	1.4	0.045	0.0098 (100)	250
17PU-H303V	3.75°	BIPOLAR	1.4	1.8	0.205 (2.1)	2.4	0.045	0.0098 (100)	250
17PU-H103V	3.75°	UNIPOLAR	1.0	4.3	0.254 (2.6)	3.2	0.056	0.0118 (120)	300
17PU-H104V	3.75°	BIPOLAR	1.0	4.3	0.294 (3.0)	7.0	0.056	0.0118 (120)	300
17PU-H106V	3.75°	UNIPOLAR	1.4	2.2	0.254 (2.6)	1.8	0.056	0.0118 (120)	300
17PU-H115V	3.75°	BIPOLAR	1.4	2.2	0.294 (3.0)	4.3	0.056	0.0118 (120)	300