

PRODUCT INFORMATION

1320nm

1A302
High-Performance LED

FM Video

The low harmonic distortion makes this device ideal for subcarrier FM video applications. Video transmission can be accomplished with minimum distortion. The double-lens optical system provides for optimum coupling of power into the fiber.





Optical and Electrical Characteristics (25° C Case Temperature)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Fiber-Coupled Power (Fig. 1, 2, & 3) (Table 1)	P_{fiber}	40	50		μW	$I_F=80\text{ mA}$ (Note 1)
Rise and Fall Time (10-90%)	t_r, t_f		3		ns	$I_F=80\text{ mA}$ (no bias)
Bandwidth (3dB _{e1})	f_c		100		MHz	$I_F=80\text{ mA}$
Harmonic Distortion (nonlinearity)	$-H_2$		26		dB	$I_F=60\text{ mA}$ $m=0.8$ $f=10\text{ MHz}$
	$-H_3$		38		dB	
Peak Wavelength	λ_p	1280	1320	1350	nm	$I_F=80\text{ mA}$
Spectral Width (FWHM)	$\Delta\lambda$		120	155	nm	$I_F=80\text{ mA}$
Forward Voltage (Fig.5)	V_F		1.5	2	V	$I_F=80\text{ mA}$
Reverse Current	I_R			100	μA	$V_R=1\text{ V}$
Capacitance	C		200		pF	$V_R=0\text{ V}, f=1\text{ MHz}$

Fiber:
62.5/125 μm
Graded
Index
NA=0.275

Note 1: Measured at the exit of 100 meters of fiber.



All dimensions in mm.

The anode is in electrical contact with the case.

TO-46 Package With Lens

Absolute Maximum Ratings

PARAMETER	SYMBOL	LIMIT
Storage Temperature	T_{stg}	-55 to +125°C
Operating Temperature (derating: Fig.4)	T_{op}	-55 to +125°C
Electrical Power Dissipation (derating: Fig.4)	P_{tot}	230 mW
Continuous Forward Current ($f \leq 10\text{ kHz}$)	I_F	110 mA
Peak Forward Current (duty cycle $\leq 50\%$, $f \geq 1\text{ MHz}$)	I_{FRM}	170 mA
Reverse Voltage	V_R	1.5 V
Soldering Temperature (2mm from the case for 10 sec)	T_{sld}	260°C

Thermal Characteristics

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Thermal Resistance - Infinite Heat Sink	R_{thjc}			100	°C/W
Thermal Resistance - No Heat Sink	R_{thja}			400	°C/W
Temperature Coefficient - Optical Power	dP/dT_j		-0.8		%/°C
Temperature Coefficient - Wavelength	$d\lambda/dT_j$		0.55		nm/°C

12368.11 1997-01-23



Europe: Tel (46) 8 58 02 45 00 Fax (46) 8 58 02 01 10
Tel (44) 1291 436180 Fax (44) 1291 436771

America: Tel 1-800-96MITEL Fax (613) 592-6909
Asia: Tel (65) 293 5312 Fax (65) 293 8527

Typical Fiber-Coupled Power		
Core Diameter/Cladding Diameter Numerical Aperture		
50/125 μm 0.20	62.5/125 μm 0.275	100/140 μm 0.29
12 μW	50 μW	90 μW

Table 1

