



Thermistor Configuration



Sample Part Number:



Interchangeable mini-BetaCURVE Probe:

Applications:

- Reduced size allows localized temperature sensing.
- Small Medical probes.
- Micro-flow sensing.
- Aerospace temperature sensing.

Features:

- Rapid Time Constant (400 milliseconds in liquids).
- Standards supplied with +/-0.2°C tolerance (0 to 70°C).
- Other tolerances available.
- 0.5 mW/°C typ. Dissipation Constant in air at 25°C.
- Smaller than regular BetaCURVE Series

The mini-BetaCURVE Probe is an extension of the BetaCURVE Series for applications that require smaller size. Although the mini-BetaCURVE Probe is packaged in polyimide tubing it is recommended that a moisture protection barrier should be used in applications where high humidity is present. The probes relatively small size allows for high precision sensing where the standard BetaCURVE series products are too large or too slow with respect to their thermal Time Constant. The size is compatible with mounting in stainless steel probe housings that have a nominal outside diameter of 1.524mm (0.06").

Interchangeable mini-BetaCURVE Probe Part Numbers and Specifications:

Part Number	Resistance @ 25 °C (Ohms)	Alpha @ 25 °C	0/50 °C Beta Value	Curve #
0.1K1MBD1	100	-3.50%	3108	1
0.3K1MBD1	300	-3.50%	3108	1
1K2MBD1	1000	-3.68%	3263	2
1K7MBD1	1000	-3.87%	3422	7
2.2K3MBD1	2252	-4.39%	3892	3
3K3MBD1	3000	-4.39%	3892	3
5K3MBD1	5000	-4.39%	3892	3
10K3MBD1	10000	-4.39%	3892	3
10K4MBD1	10000	-4.04%	3575	4
30K5MBD1	30000	-4.30%	3811	5
30K6MBD1	30000	-4.68%	4143	6
50K6MBD1	50000	-4.68%	4143	6
100K6MBD1	100000	-4.68%	4143	6
1M9MBD1	1000000	-5.18%	4582	9