

SPECIFICATION

Device Name : IGBT Module
Type Name : 1MB1600PX - 120 - 01
Spec. No. : MS5F4405

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.
 Matsumoto Factory

	DATE	NAME	APPROVED	
DRAWN	Sep. 9, '98	S. Tashiro		Fuji Electric Co., Ltd. MS5F4405 1/8
CHECKED	Sep. 9, '98	S. Miyata		
			T. Hosen	DWG. NO.


Revised Records

Date	Classification	Ind.	Content	Applied date	Drawn	Checked	Approved
Scp. 9-198	enactment	-	-	Issued date	S. Yoshimura	N. Koyama	T. HOSEN


This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

1MBI600PX-120-01

1. Outline Drawing
Unit : mm



2. Equivalent circuit



This material and its information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.

DWG. NO.

MS5F4405

3/8

H04-004-03

3. Absolute Maximum Ratings (at Tc=25°C unless otherwise specified)

Items		Symbols	Ratings	Units
Collector-Emitter voltage		V _{CE}	1200	V
Gate-Emitter voltage		V _{GE}	±20	V
Collector current	Continuous	Tc=25°C	I _c	800
		Tc=80°C		600
	1ms	Tc=25°C	I _c pulse	1600
		Tc=80°C		1200
			-I _c	600
	1ms		-I _c pulse	1200
Max. power dissipation		P _C	4100	W
Operating temperature		T _j	+150	°C
Storage temperature		T _{stg}	-40~+125	°C
Isolation voltage		V _{is}	AC 2500 (1min.)	V
Screw torque		Mounting #1	4.5	N·m
		Terminals #2	11.0	
		Terminals #3	1.7	

Note : #1 Recommendable value : 4.0±0.5 N·m (M6)

Note : #2 Recommendable value : 10.0±1.0 N·m (M8)

Note : #3 Recommendable value : 1.50±0.2 N·m (M4)

4. Electrical characteristics (at Tj=25°C unless otherwise specified)

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Zero gate voltage Collector current	I _{CE}			2.0	V _{GE} =0V, V _{CE} =1200V	mA
Gate-Emitter leakage current	I _{GES}			±0.5	V _{CE} =0V, V _{GE} =±20V	μA
Gate-Emitter threshold voltage	V _{GE(th)}	6.0	8.0	9.0	V _{CE} =20V, I _c =600mA	V
Collector-Emitter saturation voltage	V _{CE(sat)}	2.5	2.85	3.0	V _{GE} =15V, I _c =600A	V
Input capacitance	C _{ies}		60		V _{GE} =0V	nF
Output capacitance	C _{oes}		9		V _{CE} =10V	
Reverse transfer capacitance	C _{res}		4		f=1MHz	
Turn-on time	t _{on}		750	1200	V _{CE} =600V I _c =600A	ns
	t _r		200	600		
Turn-off time	t _{off}		650	1000	V _{GE} =±15V R _G =2.0Ω	
	t _f		100	300		
Diode forward on voltage	V _F	2.0		3.4	I _F =600A, V _{CE} =0V	V
Reverse recovery time	t _{rr}			350	I _F =600A	ns

5. Thermal resistance characteristics

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Thermal resistance	R _{th(j-c)}			0.03	IGBT	°C/W
	R _{th(j-c)}			0.06	Diode	
	※ R _{th(c-f)}		0.0063		the base to cooling fin	

※ This is the value which is defined mounting on the additional cooling fin with thermal compound.

Fuji Electric Co., Ltd.

DWG. NO.


MS5F4405

4/8

6. VF class

class	VF range [V]
A	2.0 ~ 2.3
B	2.2 ~ 2.5
C	2.4 ~ 2.7
D	2.6 ~ 3.0
E	2.9 ~ 3.4

7. Indication module (モジュール表示)



8. Applicable category (適用範囲)







This specification is applied to IGBT module named IMBI600PX-120-01.
 本納入仕様書は、IGBTモジュール 1MBI600PX-120-01 に適用する。

9. Storage and transportation notes (保管, 運搬上の注意事項)


- This IGBT module should be stored at a standard temperature of 5 to 35°C and humidity of 45% to 75%.
 常温保存が望ましい。
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
 急激な温度変化の無きこと。(モジュール表面が結露しないこと)
- Avoid exposure to corrosive gases and dust.
 腐蝕性ガスの発生場所、塵埃の多い場所は避けること。
- Avoid excessive external force on the module.
 製品に荷重がかからないように十分注意すること。
- Store modules with unprocessed terminals.
 モジュールの端子は未加工の状態での保管すること。
- Do not drop or otherwise shock the modules when transporting.
 製品の運搬時に衝撃を与えたり、落下させたりしないこと。

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, not used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.




Switching time vs. Gate-Resistance
 $V_{cc}=600V, I_c=600A, V_{GE} \pm 15V, T_j=25^\circ C$




Dynamic input characteristics
 $T_j=25^\circ C$




Forward current vs. Forward voltage
 $V_{GE}=0V$




Reverse recovery characteristics (t_{rr}, I_{rr} vs. I_F)
 $V_{cc}=600V, V_{GE} \pm 15V, R_G=2.0\Omega$



Transient thermal resistance



Reverse biased safety operating area
 $T_j=25\sim 125^\circ C, +V_{GE}=15V, -V_{GE} \le 15V, R_G \ge 2.0\Omega$



This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

Fuji Electric Co., Ltd.



DWG. NO.

MS5F4405

7/8

H04-004-03

This material and the information herein is the property of Fuji Electric Co., Ltd. It may not be further reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.



Fuji Electric Co., Ltd.

DWG NO.

MS5F4405

8/8

H04-004-03