

Technical Data

DIODE



maximum ratings


Voltage, Reverse (VZ)	11.0	V	NO.	1N2975RB
Voltage, Reverse Peak (VRM)		V	TYPE	10W-ZENER
Current at VR = OV (IO)		A		
Current Average Rectified (IF)	2.0	A		
Current Surge Peak (IZM)	0.78	A	CASE	DO-4_UNF
Current, Surge (IFM) at tp =		A		CATHODE TO CASE
Max. Power Dissipation (PT) at TC = 55 °C	10.0	W		
Max. Thermal Resistance (Rth J-C)	12.0	°C/W		
Max. Junction Temperature (TJ)	175.0	°C		

PERFORMANCE CHARACTERISTICS at T _c = 25°C, unless otherwise noted					
NO.	SYMBOL	CONDITIONS	MIN.	MAX.	UNITS
1.	VZ	IZ = 230.0 mA, tp = 100.0 μs, dc = 0.1 %	10.5	11.5	V
2.	RZ	IZ = 230.0 mA, ΔIZ = 10.0% IZ, f = 1.0 KHz	-	3.0	Ω
3.	RZ	IZ = 1.0 mA	-	250.0	Ω
4.	IR	VR = 8.4 V	-	5.0	μA
5.	VF	IF = 2.0 A (1)	-	1.5	V
6.					
7.					
8.					
9.					
10.					
11.					
12.					
13.					
14.					
15.					
16.					
17.					
18.					
19.					
20.					

Notes

(1)pulse-tested tp ≤ 300 μs, duty cycle ≤ 2 %

DIMENSIONS
in mm



Marking

Customer

1N2975RB

GENERAL PURPOSE