

Technical Data

DIODE



maximum ratings

Voltage, Reverse (VZ)	68.0	V	NO.	1N3040B
Voltage, Reverse Peak (VRM)		V	TYPE	1W-ZENER
Current at VR = OV (IO)		A		
Current Average Rectified (IF)		A		
Current Surge Peak (IZM)	0.014	A	CASE	DO-13
Current, Surge (IFM) at tp =		A		
Max. Power Dissipation (PT) at TC = 25 °C	1.0	W		
Max. Thermal Resistance (Rth J-A)	150.0	°C/W		
Max. Junction Temperature (TJ)	175.0	°C		


PERFORMANCE CHARACTERISTICS at T_c = 25°C, unless otherwise noted

NO.	SYMBOL	CONDITIONS	MIN.	MAX.	UNITS
1.	VZ	IZ = 3.7 mA, tp = 100.0 μs, dc = 0.1 %	64.6	71.4	V
2.	RZ	IZ = 3.7 mA, ΔIZ = 10.0 % IZ, f = 1.0 kHz	-	150.0	Ω
3.	RZ	IZ = 0.25 mA	-	2k	Ω
4.	IR	VR = 51.7 V	-	0.5	μA
5.	VF	IF = 200.0 mA (1)	-	1.5	V
6.					
7.					
8.					
9.					
10.					
11.					
12.					
13.					
14.					
15.					
16.					
17.					
18.					
19.					
20.					

Notes

(1)pulse-tested tp ≤ 300 μs, duty cycle ≤ 2 %

DIMENSIONS
in mm



Marking

Customer

1N3040B

GENERAL PURPOSE