



High-reliability discrete products
and engineering services since 1977

1N3889-1N3893

FAST RECOVERY RECTIFIER

FEATURES

- ✓ Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.
- ✓ Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding "-PBF" suffix.

MAXIMUM RATINGS

Parameter	Symbol	1N3889	1N3890	1N3891	1N3892	1N3893
Working peak reverse voltage	V_{RWM}	50V	100V	200V	300V	400V
Peak repetitive reverse voltage	V_{RRM}	50V	100V	200V	300V	400V
Operating temperature range	T_J			-65 to +175°C		
Storage temperature range	T_{stg}			-65 to +175°C		
Maximum thermal resistance	$R_{\theta JC}$			2.0°C/W junction to case		
Mounting torque				12-15 inch pounds		
Weight				.16 ounces (5.0 grams) typical		

Add "R" to part numbers for reverse polarity.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Value	Test Condition
Average forward current	$I_{F(AV)}$	12 Amps	$T_C = 100^\circ C$, square wave, $R_{\theta JC} = 2.0^\circ C/W$
Maximum surge current	I_{FSM}	175 Amps	8.3ms, half-sine, $T_C = 100^\circ C$
Maximum peak forward voltage	V_{FM}	1.50 Volts	$I_{FM} = 38A$: $T_J = 25^\circ C$ *
Maximum peak reverse current	I_{RM}	10 μA	V_{RRM} , $T_J = 25^\circ C$
Maximum peak reverse current	I_{RM}	2.0 mA	V_{RRM} , $T_J = 150^\circ C$
Maximum reverse recovery time	t_{RR}	200nS	$I_F = 1A$ dc, $V_R = 30V$, $dI/dt = 25A/\mu s$, $T_C = 55^\circ C$
Typical junction capacitance	C_J	115pF	$V_R = 10V$, $f = 1MHz$, $T_J = 25^\circ C$

✓ Pulse test: pulse width 300 μ sec. Duty cycle 2%




High-reliability discrete products
and engineering services since 1977

1N3889-1N3893

FAST RECOVERY RECTIFIER

MECHANICAL CHARACTERISTICS

Case	DO-4(R)
Marking	Alpha-numeric
Normal polarity	Cathode is stud
Reverse polarity	Anode is stud (add "R" suffix)



	DO-4(R)			
	Inches		Millimeters	
	Min	Max	Min	Max
A	-	0.078	-	1.981
B	0.422	0.453	10.719	11.506
C	-	0.405	-	10.287
D	-	0.800	-	20.320
E	0.420	0.440	10.668	11.176
F	-	0.250	-	6.350
G	-	0.424	-	10.770
H	0.066	-	1.676	-



High-reliability discrete products
and engineering services since 1977

1N3889-1N3893

FAST RECOVERY RECTIFIER

Figure 1
Typical Forward Characteristics




Figure 2
Typical Reverse Characteristics




Figure 3
Typical Junction Capacitance




Figure 4
Forward Current Derating

