

Technical Data

DIODE



maximum ratings


Voltage, Reverse (VZ)	5.6	V	NO.	1N3997A
Voltage, Reverse Peak (VRM)		V	TYPE	ZENER
Current at VR = OV (IO)		A		
Current Average Rectified (IF)	2.0	A		
Current Surge Peak (IZM)	1.62	A	CASE	DO-4_UNF
Current, Surge (IFM) at tp =		A		CATHODE TO CASE
Max. Power Dissipation (PT) at TC = 55 °C	10.0	W		
Max. Thermal Resistance (Rth J-C)	1.2	°C/W		
Max. Junction Temperature (TJ)	175.0	°C		

PERFORMANCE CHARACTERISTICS at T _c = 25°C, unless otherwise noted					
NO.	SYMBOL	CONDITIONS	MIN.	MAX.	UNITS
1.	VZ	IZ = 0.45 A, tp = 100.0 μs, dc = 0.1 %	5.32	5.88	V
2.	RZ	IZ = 0.45 A, Δ IZ = 10.0 % IZ, f = 1.0 kHz	-	1.0	Ω
3.	IR	VR = 1.0 V	-	10.0	μA
4.	VF	IF =2.0 A (1)	-	1.5	V
5.					
6.					
7.					
8.					
9.					
10.					
11.					
12.					
13.					
14.					
15.					
16.					
17.					
18.					
19.					
20.					

Notes

(1)pulse-tested tp ≤ 300 μs, duty cycle ≤ 2 %

DIMENSIONS
in mm



Marking

Customer

1N3997A

GENERAL PURPOSE