

SWITCHING RECTIFIERS

FEATURES

- Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.
- Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding "-PBF" suffix.

MAXIMUM RATINGS

Parameter	Symbol	1N								
		4149	4151	4152	4153	4154	4446	4447	4448	4449
Peak reverse voltage	V_{RM}	75V	75V	40V	75V	35V	75V	75V	75V	75V
Average rectified current	I_o	200mA								
Forward surge current, 8.3ms	I_{FSM}	500mA								
Operating junction temperature range	T_J	-65° to 150°C								
Storage temperature range	T_{stg}	-65° to 200°C								

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Part number	Peak inverse voltage	Maximum forward voltage					Reverse current		Reverse current		Junction capacitance	Reverse recovery time
	PIV	V_F					I_{R1}	I_{R2}	C_J	t_{rr}		
											$T_A = 150^\circ\text{C}$	
	Vdc	@10mA	@20mA	@30mA	@50mA	@100mA	Min	Max	Min	Max	pF	ns
1N4149		75	1.0	-	-	-	-	20	25	20		
1N4151	75	-	-	-	1.0	-	50	50	50	50	4	2
1N4152	40	0.81	0.88	-	-	-	-	50	-	50	2	2
1N4153	75	0.81	0.88	-	-	-	-	50	-	50	2	2
1N4154	35	-	-	1.0	-	-	25	100	25	100	4	2
1N4446	75	-	1.0	-	-	-	20	25	20	50	4	4
1N4447	75	-	1.0	-	-	-	20	25	20	50	4	4
1N4448	75	-	-	-	-	1.0	20	25	20	50	4	4
1N4449	75	-	-	1.0	-	-	20	25	20	50	2	4




High-reliability discrete products
and engineering services since 1977

1N4149, 1N4151-1N4154,
1N4446-1N4449

SWITCHING RECTIFIERS

MECHANICAL CHARACTERISTICS

Case:	DO-35
Marking:	Body painted, alpha-numeric
Polarity:	Cathode band



	DO-35			
	Inches		Millimeters	
	Min	Max	Min	Max
BD	0.065	0.090	1.400	2.290
BL	0.120	0.200	3.050	5.080
LD	0.018	0.022	0.460	0.560
LL	1.000	1.500	25.400	38.100