


DESCRIPTION

The popular 1N746 thru 1N759A and 1N4370 thru 1N4372A series of 0.5 watt Zener Voltage Regulators provides a selection from 2.4 to 12 volts in standard 5% or 10% tolerances as well as tighter tolerances identified by different suffix letters on the part number. These glass axial-leaded DO-35 Zeners are also available with an internal-metallurgical-bond option by adding a "-1" suffix as well as RoHS Compliant by adding an "e3" suffix. Microsemi also offers numerous other Zener products to meet higher and lower power applications.

IMPORTANT: For the most current data, consult MICROSEMI's website: <http://www.microsemi.com>

APPEARANCE

**DO-35
(DO-204AH)**



FEATURES

- JEDEC registered 1N746 thru 1N759A and 1N4370 thru 1N4372A series
- Internal metallurgical bond option available by adding a "-1" suffix similar to military devices
- Commercial Surface Mount equivalents available as MLL746 to MLL759A and MLL4370 to MLL4372A including the "-1" suffix in the DO-213AA MELF style package (consult factory for others)
- RoHS Compliant devices available by adding "e3" suffix
- DO-7 glass body axial-leaded Zener equivalents are also available

MAXIMUM RATINGS

- Operating and Storage temperature: -65°C to $+175^{\circ}\text{C}$
- Thermal Resistance: 250°C/W junction to lead at 3/8 (10 mm) lead length from body, or 310°C/W junction to ambient when mounted on FR4 PC board (1 oz Cu) with 4 mm^2 copper pads and track width 1 mm, length 25 mm
- Steady-State Power: 0.5 watts at $T_L \leq 50^{\circ}\text{C}$ 3/8 inch (10 mm) from body or 0.48 W at $T_A \leq 25^{\circ}\text{C}$ when mounted on FR4 PC board as described for thermal resistance above (also see Figure1)
- Forward voltage @200 mA: 1.1 volts
- Solder Temperatures: 260°C for 10 s (max)

APPLICATIONS / BENEFITS

- Regulates voltage over a broad operating current and temperature range
- Selection from 2.4 to 12 V
- Standard voltage tolerances are plus/minus 5% with A suffix identification and 10 % with no suffix
- Tight tolerances available in plus or minus 2% or 1% with C or D suffix respectively
- Flexible axial-lead mounting terminals
- Nonsensitive to ESD per MIL-STD-750 Method 1020
- Minimal capacitance (see Figure 3)
- Inherently radiation hard as described in Microsemi MicroNote 050

MECHANICAL AND PACKAGING

- CASE: Hermetically sealed axial-lead glass DO-35 (DO-204AH) package
- TERMINALS: Tin-Lead or RoHS Compliant annealed matte-Tin plating solderable per MIL-STD-750, method 2026
- POLARITY: Cathode indicated by band. Diode to be operated with the banded end positive with respect to the opposite end for Zener regulation
- MARKING: Part number
- TAPE & REEL option: Standard per EIA-296 (add "TR" suffix to part number)
- WEIGHT: 0.2 grams
- See package dimensions on last page

ELECTRICAL CHARACTERISTICS* @ 25°C

| JEDEC TYPE NO. (NOTE 1) | NOMINAL ZENER VOLTAGE V_Z @ I_{ZT} (NOTE 2) VOLTS | ZENER TEST CURRENT I_{ZT} mA | MAXIMUM ZENER IMPEDANCE Z_{ZT} @ I_{ZT} (NOTE 3) OHMS | MAXIMUM REVERSE CURRENT I_R @ $V_R = 1$ VOLT | | MAXIMUM ZENER CURRENT I_{ZM} (NOTE 4) mA | TYPICAL TEMP COEFF. OF ZENER VOLTAGE α_{VZ} %/°C |
|----------------------------|--|-----------------------------------|--|--|---------|---|--|
| | | | | @25°C | @+150°C | | |
| | | | | μA | μA | | |
| 1N4370 | 2.4 | 20 | 30 | 100 | 200 | 150 | -.085 |
| 1N4371 | 2.7 | 20 | 30 | 75 | 150 | 135 | -.080 |
| 1N4372 | 3.0 | 20 | 29 | 50 | 100 | 120 | -.075 |
| 1N746 | 3.3 | 20 | 28 | 10 | 30 | 110 | -.066 |
| 1N747 | 3.6 | 20 | 24 | 10 | 30 | 100 | -.058 |
| 1N748 | 3.9 | 20 | 23 | 10 | 30 | 95 | -.046 |
| 1N749 | 4.3 | 20 | 22 | 2 | 30 | 85 | -.033 |
| 1N750 | 4.7 | 20 | 19 | 2 | 30 | 75 | -.015 |
| 1N751 | 5.1 | 20 | 17 | 1 | 20 | 70 | +/- .010 |
| 1N752 | 5.6 | 20 | 11 | 1 | 20 | 65 | + .030 |
| 1N753 | 6.2 | 20 | 7 | .1 | 20 | 60 | + .049 |
| 1N754 | 6.8 | 20 | 5 | .1 | 20 | 55 | + .053 |
| 1N755 | 7.5 | 20 | 6 | .1 | 20 | 50 | + .057 |
| 1N756 | 8.2 | 20 | 8 | .1 | 20 | 45 | + .060 |
| 1N757 | 9.1 | 20 | 10 | .1 | 20 | 40 | + .061 |
| 1N758 | 10.0 | 20 | 17 | .1 | 20 | 35 | + .062 |
| 1N759 | 12.0 | 20 | 30 | .1 | 20 | 30 | + .062 |

* JEDEC Registered Data

NOTE 1: Standard tolerance on JEDEC types shown is +/- 10%. Suffix letter A denotes +/- 5% tolerance; suffix letter C denotes +/- 2%; and suffix letter D denotes +/- 1% tolerance.

NOTE 2: Voltage measurements to be performed 20 seconds after application of dc test current.

NOTE 3: Zener impedance derived by superimposing on I_{ZT} , a 60 cps, rms ac current equal to 10% I_{ZT} (2mA ac). See MicroNote 202 for typical zener impedance variation with different operating currents.

NOTE 4: Allowance has been made for the increase in V_Z due to Z_Z and for the increase in junction temperature as the unit approaches thermal equilibrium at the power dissipation of 400 mW.

GRAPHS




FIGURE 1
POWER DERATING CURVE




FIGURE 2
ZENER VOLTAGE TEMPERATURE COEFFICIENT vs. ZENER VOLTAGE




FIGURE 3
CAPACITANCE vs. ZENER VOLTAGE
(TYPICAL)

