



## 1N60-KW

Power MOSFET

### 1A, 600V N-CHANNEL POWER MOSFET



#### DESCRIPTION

The UTC 1N60-KW is a high voltage MOSFET and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and have a high rugged avalanche characteristics. This power MOSFET is usually used at high speed switching applications in power supplies, PWM motor controls, high efficient DC to DC converters and bridge circuits.

#### FEATURES

- \*  $R_{DS(ON)} < 15\Omega @ V_{GS}=10V, I_D=0.5A$
- \* Fast switching capability
- \* Avalanche energy specified
- \* Improved dv/dt capability, high ruggedness

#### SYMBOL







#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
-	1N60G-AA3-R	SOT-223	G	D	S	Tape Reel
-	1N60G-AB3-R	SOT-89	G	D	S	Tape Reel
1N60L-TM3-T	1N60G-TM3-T	TO-251	G	D	S	Tube
1N60L-TN3-R	1N60G-TN3-R	TO-252	G	D	S	Tape Reel
1N60L-T92-B	1N60G-T92-B	TO-92	G	D	S	Tape Box
1N60L-T92-K	1N60G-T92-K	TO-92	G	D	S	Bulk

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>1N60G-AA3-R</p>	<p>(1) T: Tube, R: Tape Reel, B: Tape Box, K: Bulk  (2) AA3: SOT-223, AB3: SOT-89, TM3: TO-251  TN3: TO-252, T92: TO-92  (3) L: Lead Free, G: Halogen Free and Lead Free</p>
--------------------	--

## MARKING

<p style="text-align: center;">SOT-223</p> 	<p style="text-align: center;">SOT-89</p> 
<p style="text-align: center;">TO-251 / TO-252</p> 	<p style="text-align: center;">TO-92</p> 

■ **ABSOLUTE MAXIMUM RATINGS** ( $T_C = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		$V_{DSS}$	600	V
Gate-Source Voltage		$V_{GSS}$	$\pm 30$	V
Continuous Drain Current		$I_D$	1	A
Avalanche Energy	Single Pulsed (Note 2)	$E_{AS}$	23	mJ
Peak Diode Recovery dv/dt (Note 3)		dv/dt	4.5	V/ns
Power Dissipation ( $T_A=25^\circ\text{C}$ )	SOT-89	$P_D$	0.69	W
	SOT-223		0.8	W
	TO-251/TO-252		1.1	W
	TO-92		0.6	W
Junction Temperature		$T_J$	+150	$^\circ\text{C}$
Operating Temperature		$T_{OPR}$	-55 ~ +150	$^\circ\text{C}$
Storage Temperature		$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2.  $L = 46\text{mH}$ ,  $I_{AS} = 1\text{A}$ ,  $V_{DD} = 50\text{V}$ ,  $R_G = 25\Omega$ , Starting  $T_J = 25^\circ\text{C}$

3.  $I_{SD} \leq 1.2\text{A}$ ,  $di/dt \leq 200\text{A}/\mu\text{s}$ ,  $V_{DD} \leq BV_{DSS}$ , Starting  $T_J = 25^\circ\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOT-89	$\theta_{JA}$	180	$^\circ\text{C}/\text{W}$
	SOT-223		150	$^\circ\text{C}/\text{W}$
	TO-251/TO-252		110	$^\circ\text{C}/\text{W}$
	TO-92		180	$^\circ\text{C}/\text{W}$
Junction to Case	SOT-89	$\theta_{JC}$	38	$^\circ\text{C}/\text{W}$
	SOT-223		14	$^\circ\text{C}/\text{W}$
	TO-251/TO-252		4.53	$^\circ\text{C}/\text{W}$
	TO-92		88	$^\circ\text{C}/\text{W}$

■ **ELECTRICAL CHARACTERISTICS** ( $T_C=25^\circ\text{C}$ , unless otherwise specified.)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	600			V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=600V, V_{GS}=0V$			10	$\mu A$
Gate-Source Leakage Current	Forward	$I_{GSS}$			100	nA
	Reverse				-100	nA
Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS}/\Delta T_J$	$I_D=250\mu A$		0.4		$V/^\circ C$
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0		4.0	V
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=0.5A$		12	15	$\Omega$
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	$C_{ISS}$	$V_{DS}=25V, V_{GS}=0V, f=1MHz$		150		pF
Output Capacitance	$C_{OSS}$			17.5		pF
Reverse Transfer Capacitance	$C_{RSS}$			4.6		pF
<b>SWITCHING CHARACTERISTICS</b>						
Total Gate Charge	$Q_G$	$V_{DS}=50V, I_D=1.3A, R_G=3.3k\Omega$ $V_{GS}=10V, (Note\ 2,3)$		8		nC
Gate-Source Charge	$Q_{GS}$			1.8		nC
Gate-Drain Charge	$Q_{GD}$			1.3		nC
Turn-On Delay Time	$t_{D(ON)}$	$V_{DD}=30V, I_D=1A, R_G=25\Omega,$ $V_{GS}=10V (Note\ 2,3)$		15		ns
Turn-On Rise Time	$t_R$			30		ns
Turn-Off Delay Time	$t_{D(OFF)}$			26		ns
Turn-Off Fall Time	$t_F$			35		ns
<b>SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS</b>						
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V, I_S=1A$			1.4	V
Maximum Continuous Drain-Source Diode Forward Current	$I_S$				1.0	A
Maximum Pulsed Drain-Source Diode Forward Current	$I_{SM}$				4.0	A

Notes: 1. Repetitive Rating: Pulse width limited by maximum junction temperature


2. Pulse Test: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2\%$

3. Essentially Independent of Operating Temperature

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


## TEST CIRCUITS AND WAVEFORMS (Cont.)




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform



Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.