

UTC UNISONIC TECHNOLOGIES CO., LTD

1SS400 Preliminary DIODE

SWITCHING DIODE


DESCRIPTION

The UTC 1SS400 is a switching diode, it uses UTC's advanced technology to provide customers with high speed switching and low reverse leakage, etc.

FEATURES

- * High speed switching
- * Low reverse leakage
- **SYMBOL**







ORDERING INFORMATION

Ordering Number		Doolsono	Pin Assignment		Dooking	
Lead Free	Halogen Free	Package	1	2	Packing	
1SS400L-CC2-R	1SS400G-CC2-R	SOD-523	Α	K	Tape Reel	

Note: Pin Assignment: A: Anode, K: Cathode



MARKING



www.unisonic.com.tw 1 of 3

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT	
DC Blocking Voltage	V_{R}	80	V	
Peak Repetitive Reverse Voltage	V_{RRM}	90	V	
Average Rectified Output Current	lo	100	mA	
Power Dissipation	P_D	150	mW	
Operating Junction Temperature	TJ	-55~+125	°C	
Storage Temperature	T _{STG}	125	°C	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Forward Voltage	V_{F}	I _F =100mA			1.2	V
Reverse Leakage Current	I _R	V _R =80V			0.1	μΑ
Reverse Recovery Time	T_RR	$V_R=6V$, $I_F=10$ mA, $R_L=100$ Ω			4	ns

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.