


PIN Diode for VHF, UHF, AGC Applications

1SV250

■ Features

- Small-sized package facilitates high-density mounting and permits 1SV250-applied equipment to be made smaller.
- Small interterminal capacitance ($C=0.23\text{pF}$ typ).
- Small forward series resistance ($r_s=4.5\ \Omega$ max).

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Value	Unit
Reverse voltage	V_R	50	V
Forward current	I_F	50	mA
Allowable power dissipation	P	150	mW
Junction temperature	T_j	125	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +125	$^\circ\text{C}$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse voltage	V_R	$I_R = 10\ \mu\text{A}$	50			V
Reverse current	I_R	$V_R = 50\text{V}$			0.1	μA
Forward Voltage	V_F	$I_F = 50\text{mA}$		0.92	4.5	V
Interterminal Capacitance	C	$V_R = 50\text{V}, f = 1\text{MHz}$		0.23		pF
Series Resistance	r_s	$I_F = 10\text{mA}, f = 100\text{MHz}$				Ω

■ Marking

Marking	FV
---------	----