



2CL3509H、2CL3512H


微波爐用高壓二極管 High Voltage Diodes for Micro-Wave Oven

■特徵 Features

- $I_F(AV)$ 350mA
- V_{RRM} 9kV, 12kV
- 高可靠性 High reliability

■外形尺寸和印記 Outline Dimensions and Mark

單位 Unit: mm



■用途 Applications

- 微波爐及其他電子設備高壓電源整流用
Rectification for high voltage power supply
of magnetron in Micro wave oven and others

型號 Type	代號 Code	負極標誌 Cathode Mark
2CL3509H	T3509H	
2CL3512H	T3512H	

■極限值 (絕對最大額定值)

Limiting Values (Absolute Maximum Rating)

參數名稱 Item	符號 Symbol	單位 Unit	2CL3509H	2CL3512H
反向重複峰值電壓 Repetitive Peak Reverse Voltage	V_{RRM}	kV	9	12
正向平均電流 Average Forward Current	$I_{F(AV)}$	mA	350 (正弦半波 50Hz, 電阻負載, $T_a \leq 60^\circ\text{C}$ *) (50Hz Half-sine wave, Resistance load, $T_a \leq 60^\circ\text{C}$)	
正向浪湧電流 Forward Surge Current	I_{FSM}	A	30 (正弦半波 50Hz, 一個周期, $T_a = 25^\circ\text{C}$) (50Hz Half-sine wave, 1cycle, $T_a = 25^\circ\text{C}$)	
反向浪湧電流 Reverse Surge Current	I_{RSM}	mA	100 (方波、 $W_p=1\text{ms}$, 單脈衝, $T_a = 25^\circ\text{C}$) ($W_p=1\text{ms}$, Rectangular-wave, One-shot, $T_a = 25^\circ\text{C}$)	
有效結溫 Virtual Junction Temperature	$T_{(vj)}$	°C		130
貯存溫度 Storage Temperature	T_{stg}	°C		-40 ~ +130


* 散熱方式：將負極端子固定在厚度為0.6mm,面積為50mm×50mm以上的散熱片上，風冷條件：0.5m/s。

Cooling Requirement: Cathode terminal is fastened to radiating fin that size is more than 50mm×50mm×0.6mm Wind-cooled velocity is more than 0.5m/s





■電特性 ($T_a=25^\circ\text{C}$ 除非另有規定)

Electrical Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified)


參數名稱 Item	符號 Symbol	單位 Unit	測試條件 Test Condition	2CL3509H	2CL3512H
正向峰值電壓 Peak Forward Voltage	V_{FM}	V	$I_{FM}=350\text{mA}$	≤ 10	≤ 12
反向峰值電流 Peak Reverse Current	I_{RRM1}	μA	$V_{RM}=V_{RRM}$	≤ 5	
雪崩擊穿電壓 Avalanche Breakdown Voltage	$V_{(BR)}$	kV	$I_R=100\text{ }\mu\text{A}$	≥ 9.5	≥ 12.5



■特性曲線（典型） Characteristics(Typical)

正向特性
Forward Characteristics反向特性
Reverse Characteristics正向平均電流降額曲線
I_{F(AV)} — T_a Derating擊穿電壓分佈
Breakdown Voltage Distribution

• 安全試驗 Safety Test



寬 3mm 金屬箔卷在管體中央

3mm Wide metal film is rolled on the surface
middle of diode body

1.絕緣電阻試驗：AB之間施加500V 直流電壓，用絕緣電阻表測，絕緣電阻大於1000MΩ。

2.耐壓強度試驗：在絕緣油中進行，AB之間施加峰值為15kV的正弦半波電壓、1分鐘，無擊穿或飛弧。

1. Insulation Resistance Test: 500V DC voltage is added between A and B. The measurement by insulation resistance meter is big than 1000MΩ.

2. Resistance To Voltage Strength Test: 15kV half-sine wave voltage is added between A and B for one minute and no breakdown or arc in insulation oil.