


**2KG037075PJL COMMON ANODE DOUBLE DICE SWITCHING DIODE CHIPS****DESCRIPTION**

- 2KG037075PJL is a common anode double-dice switching diode fabricated in planar technology.
- The parameters of diode match well due to double dice on the same chip substrate.
- Optimized graph design suit for encapsulation bonding, and the interference is very small between two dice.
- The top electrodes material is Al, and the back-side electrodes material is Au.
- Chip size: 0.37 X 0.37 (mm)<sup>2</sup>.



2KG037075PJL CHIP TOPOGRAPHY

**2KG037075PJL ELECTRICAL CHARACTERISTICS (T<sub>J</sub>=25°C)**

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =10mA.	--	--	1.0	V
		I <sub>F</sub> =100mA.	0.62	0.9	1.2	V
Reverse Voltage	V <sub>BR</sub>	I <sub>B</sub> =100μA.	100	120	--	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =20V.	--	--	25	nA
		V <sub>R</sub> =75V.	--	--	5	μA
Diode Capacitance	C <sub>d</sub>	f=1MHz; V <sub>R</sub> =0.	--	1.9	4	pF
Reverse Recovery Time	t <sub>rr</sub>	When switched from I <sub>F</sub> =10mA to V <sub>R</sub> =6V; R <sub>L</sub> =100Ω; measured at I <sub>R</sub> =1mA.	--	--	4	ns

Note: The electrical characteristic is single dice value.