

isc Silicon PNP Power Transistor


2N3195

DESCRIPTION

- Excellent Safe Operating Area
- With TO-3 package
- Low collector saturation voltage
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


APPLICATIONS

- For medium-speed switching and amplifier applications



ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CB0}	Collector-Base Voltage	-40	V
V _{CEO}	Collector-Emitter Voltage	-40	V
V _{EBO}	Emitter-Base Voltage	-10	V
I _c	Collector Current-Continuous	-5	A
P _c	Collector Power Dissipation@T _c =25°C	75	W
T _J , T _{stg}	Operating and Storage Junction Temperature Range	-65~+200	°C



THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	1.17	°C/W

isc Silicon PNP Power Transistors**2N3195****ELECTRICAL CHARACTERISTICS** $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = -3A; I_B = -0.6A$		-0.9	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = -3A; V_{CE} = -0.6V$		-1.9	V
I_{CEO}	Collector Cutoff Current	$V_{CE} = -40V; I_B = 0$		-5.0	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB} = -5V; I_C = 0$		-1.0	mA
h_{FE}	DC Current Gain	$I_C = -3A; V_{CE} = -3V$	10	30	

Notice:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.