

# 2N3439

## Product Preview Low Power Transistor

### NPN Silicon

#### Features

- MIL-PRF-19500/368 Qualified
- Available as JAN, JANTX, and JANTXV
- Hermetically Sealed Commercial Product with Option for Military Temperature Range Screening

#### MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Value	Unit
Collector - Emitter Voltage	$V_{CEO}$	350	Vdc
Collector - Base Voltage	$V_{CBO}$	450	Vdc
Emitter - Base Voltage	$V_{EBO}$	7.0	Vdc
Collector Current - Continuous	$I_C$	1.0	Adc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$	$P_T$	800	mW
Total Device Dissipation @ $T_C = 25^\circ\text{C}$	$P_T$	5.0	W
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-65 to +200	$^\circ\text{C}$

#### THERMAL CHARACTERISTICS



Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	175	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction to Case	$R_{\theta JC}$	30	$^\circ\text{C}/\text{W}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.



ON Semiconductor®

<http://onsemi.com>



TO-39  
CASE 205AB  
STYLE 1

#### ORDERING INFORMATION

Device	Package	Shipping
2N3439	TO-39	Bulk

This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.

## 2N3439

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)




Characteristic	Symbol	Min	Max	Unit
<b>ON CHARACTERISTICS</b>				
Emitter-Base Cutoff Current ( $V_{EB} = 7.0 \text{ Vdc}$ )	$I_{EBO}$	-	10	$\mu\text{Adc}$
Collector-Emitter Cutoff Current ( $V_{CE} = 300 \text{ Vdc}$ )	$I_{CEO}$	-	2.0	$\mu\text{Adc}$
Collector-Emitter Cutoff Current ( $V_{CE} = 450 \text{ Vdc}$ , $V_{BE} = -1.5 \text{ Vdc}$ )	$I_{CEX}$	-	5.0	$\mu\text{Adc}$
Collector-Base Cutoff Current ( $V_{CE} = 360 \text{ Vdc}$ ) ( $V_{CE} = 450 \text{ Vdc}$ ) ( $V_{CE} = 360 \text{ Vdc}$ , $T_A = 150^\circ\text{C}$ )	$I_{CBO}$	- - -	2.0 5.0 6.0	$\mu\text{Adc}$
DC Current Gain (Note 1) ( $I_C = 0.2 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ ) ( $I_C = 2.0 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ ) ( $I_C = 20 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ ) ( $I_C = 20 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ , $T_A = -55^\circ\text{C}$ )	$h_{FE}$	10 30 40 15	- - 160 -	-
Collector-Emitter Saturation Voltage (Note 1) ( $I_C = 50 \text{ mAdc}$ , $I_B = 4.0 \text{ mAdc}$ )	$V_{CE(sat)}$	-	0.5	Vdc
Base-Emitter Saturation Voltage (Note 1) ( $I_C = 50 \text{ mAdc}$ , $I_B = 4.0 \text{ mAdc}$ )	$V_{BE(sat)}$	-	1.3	Vdc
<b>SMALL-SIGNAL CHARACTERISTICS</b>				
Output Capacitance ( $V_{CB} = 10 \text{ Vdc}$ , $I_E = 0$ , $100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$ )	$C_{obo}$	-	10	pF
Input Capacitance ( $V_{CB} = 5.0 \text{ Vdc}$ , $I_E = 0$ , $100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$ )	$C_{ibo}$	-	75	pF
Small-Signal Short-Circuit Forward Current Transfer Ratio ( $I_C = 5.0 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ , $f = 1.0 \text{ kHz}$ )	$h_{fe}$	25	-	-
Small-Signal Current Gain ( $I_C = 10 \text{ mAdc}$ , $V_{CE} = 10 \text{ Vdc}$ , $f = 5.0 \text{ MHz}$ )	$ h_{fe} $	3.0	15	-
<b>SWITCHING CHARACTERISTICS</b>				
Turn-on Time (Note 2) ( $V_{CC} = 200 \text{ Vdc}$ , $I_C = 20 \text{ mAdc}$ , $I_{B1} = 2.0 \text{ mAdc}$ )	$t_{on}$	-	1.0	$\mu\text{s}$
Turn-off Time (Note 2) ( $V_{CC} = 200 \text{ Vdc}$ , $I_C = 20 \text{ mAdc}$ , $I_{B1} = -I_{B2} = 2.0 \text{ mAdc}$ )	$t_{off}$	-	10	$\mu\text{s}$

1. Pulse Test: See section 4 of MIL-STD-750.

2. See Figure 14 in MIL-PRF-19500/368.

PACKAGE DIMENSIONS

TO-39 3-Lead  
CASE 205AB-01  
ISSUE O



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION J MEASURED FROM DIAMETER A TO EDGE.
4. LEAD TRUE POSITION TO BE DETERMINED AT THE GAUGE PLANE DEFINED BY DIMENSION R.
5. DIMENSION F APPLIES BETWEEN DIMENSION P AND L.
6. DIMENSION D APPLIES BETWEEN DIMENSION L AND K.
7. BODY CONTOUR OPTIONAL WITHIN ZONE DEFINED BY DIMENSIONS A, B, AND T.
8. DIMENSION B SHALL NOT VARY MORE THAN 0.010 IN ZONE P.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	8.89	9.40	0.350	0.370
B	8.00	8.51	0.315	0.335
C	6.10	6.60	0.240	0.260
D	0.41	0.48	0.016	0.019
E	0.23	3.18	0.009	0.125
F	0.41	0.48	0.016	0.019
H	0.71	0.86	0.028	0.034
J	0.73	1.02	0.029	0.040
K	12.70	14.73	0.500	0.580
L	6.35	---	0.250	---
M	---	---	45° BSC	45° BSC
N	5.08 BSC	---	0.200 BSC	---
P	---	1.27	---	0.050
R	1.37 BSC	---	0.054 BSC	---
T	---	0.76	---	0.030
U	2.54	---	0.100	---

STYLE 1:

1. PIN 1. EMITTER
2. BASE
3. COLLECTOR

ON Semiconductor and  $\text{ON}$  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative