



NPN 2N3442 – 2N4347

HIGH POWER INDUSTRIAL TRANSISTORS

NPN silicon transistors in Jedec TO-39 metal case.

They are designed for applications in industrial and commercial equipment including high fidelity audio amplifiers, series and shunts regulators and power switches.

Low Collector-Emitter Saturation Voltage.

Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit
V_{CEO}	Collector-Emitter Voltage		2N4347 120	V
			2N3442 140	
V_{CB}	Collector-Base Voltage		2N4347 140	V
			2N3442 160	
V_{EB}	Emitter-Base Voltage		2N4347 7	V
			2N3442	
I_C	Collector Current	Continuous	2N4347 5	A
			2N3442 10	
		Peak	2N4347 10	
			2N3442 15 (**)	
I_B	Base Current	Continuous	2N4347 3	A
			2N3442 7	
		Peak	2N4347 8	
			2N3442 -	
P_D	Total Device Dissipation	@ $T_C = 25^\circ$	2N4347 100	W
			2N3442 117	
		Derate above 25°	2N4347 0.57	W/°C
			2N3442 0.67	
T_J	Junction Temperature		2N4347 -65 to +200	°C
			2N3442	
T_S	Storage Temperature		2N4347 -65 to +200	°C
			2N3442	

(**) This data guaranteed in addition to JEDEC registered data.

THERMAL CHARACTERISTICS

Symbol	Ratings		Value	Unit
R_{thJC}	Thermal Resistance, Junction to Case		2N4347 1.75	°C/W
			2N3442 1.5	

NPN 2N3442 – 2N4347

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted


Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit	
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage (*)	$I_C=200\text{ mA}, I_B=0$	2N4347	120	-	-	V
			2N3442	140	-	-	
I_{CEO}	Collector-Emitter Current	$V_{CE}=100\text{ V}, I_B=0$	2N4347	-	-	200	mA
		$V_{CE}=140\text{ V}, I_B=0$	2N3442			200	
I_{CEX}	Collector Cutoff Current	$V_{CE}=125\text{ V}, V_{EB(off)}=1.5\text{ V}$	2N4347	-	-	2.0	mA
		$V_{CE}=120\text{ V}, V_{EB(off)}=1.5\text{ V}$ $T_C = 150^\circ\text{C}$				10	
		$V_{CE}=140\text{ V}, V_{EB(off)}=1.5\text{ V}$	2N3442	-	-	5.0	
		$V_{CE}=140\text{ V}, V_{EB(off)}=1.5\text{ V}$ $T_C = 150^\circ\text{C}$				30	
I_{EBO}	Emitter Cutoff Current	$V_{BE}=7\text{ V}, I_C=0$	2N4347	-	-	5.0	mA
			2N3442				
h_{FE}	DC Current Gain	$I_C=2\text{ A}, V_{CE}=4.0\text{ V}$	2N4347	15	-	60	-
		$I_C=5\text{ A}, V_{CE}=4\text{ V}$					
		$I_C=3\text{ A}, V_{CE}=4\text{ V}$	2N3442	20	-	70	
		$I_C=10\text{ A}, V_{CE}=4\text{ V}$					
$V_{CE(SAT)}$	Collector-Emitter saturation Voltage	$I_C=2\text{ A}, I_B=200\text{ mA}$	2N4347	-	-	1.0	V
		$I_C=5\text{ A}, I_B=630\text{ mA}$				2.0	
		$I_C=10\text{ A}, I_B=200\text{ mA}$	2N3442	-	-	5.0	
$V_{BE(on)}$	Base-Emitter Voltage	$I_C=2\text{ A}, V_{CE}=4\text{ V}$	2N4347	-	-	2.0	V
		$I_C=5\text{ A}, V_{CE}=4\text{ V}$				3.0	
		$I_C=10\text{ A}, V_{CE}=4\text{ V}$	2N3442	-	-	5.7	
h_{fe}	Small Signal Current Gain	$V_{CE}=4\text{ V}, I_C=500\text{ mA}$ $f=1\text{ kHz}$	2N4347	40	-	-	-
		$V_{CE}=4\text{ V}, I_C=2\text{ A}$ $f=1\text{ kHz}$	2N3442	12	-	72	
$V_{CER(SUS)}$	Collector-Emitter Sustaining Voltage $R_{BE}=100\Omega$	$I_C=100\text{ mA}$	2N4347	130	-	-	V
		$I_C=200\text{ mA}$					
		$I_C=100\text{ mA}$	2N3442	-	-	-	
		$I_C=200\text{ mA}$				150	
f_T	Current Gain – Bandwidth Product	$V_{CE}=4\text{ V}, I_C=500\text{ mA}$ $f_{test} = 50\text{ kHz}$	2N4347	200	-	-	kHz
		$V_{CE}=4\text{ V}, I_C=500\text{ mA}$ $f_{test} = 50\text{ kHz}$	2N3442	80	-	-	
$I_{s/b}$	Second Breakdown Collector Current	$V_{CE}=67\text{ V}, I_C=1.5\text{ A}$	2N4347	1.0	-	-	s
		$V_{CE}=78\text{ V}, I_C=1.5\text{ A}$	2N3442	1.0	-	-	

(*) Pulse Width $\approx 300\ \mu\text{s}$, Duty Cycle $\angle 2.0\%$


NPN 2N3442 – 2N4347

MECHANICAL DATA CASE TO-3

DIMENSIONS (mm)		
	min	max
A	11	13.10
B	0.97	1.15
C	1.5	1.65
D	8.32	8.92
F	19	20
G	10.70	11.1
N	16.50	17.20
P	25	26
R	4	4.09
U	38.50	39.30
V	30	30.30



Pin 1 :	Base
Pin 2 :	Emitter
Case :	Collector



Revised September 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.