

2N3634 thru 2N3637

**JAN, JTX AVAILABLE
CASE 79, STYLE 1
TO-39 (TO-39-205AD)**

**HIGH VOLTAGE
TRANSISTOR**

PNP SILICON

4

MAXIMUM RATINGS

Rating	Symbol	2N3634	2N3636	Unit
		2N3635	2N3637	
Collector-Emitter Voltage	V _{CEO}	140	175	Vdc
Collector-Base Voltage	V _{CBO}	140	175	Vdc
Emitter-Base Voltage	V _{EBO}	5.0		Vdc
Collector Current — Continuous	I _C	1.0		Adc
Total Device Dissipation @ T _A = 25°C Derate above 25°C	P _D	1.0	1.0	Watt
		5.71		mW/°C
Total Device Dissipation @ T _C = 25°C Derate above 25°C	P _D	5.0	5.0	Watts
		28.6		mW/°C
Operating and Storage Junction Temperature Range	T _J , T _{stg}	-65 to +200		°C

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage(1) (I _C = 10 mAdc, I _B = 0)	V _{(BR)CEO}	140 175	— —	Vdc
		2N3634, 2N3635 2N3636, 2N3637		
Collector-Base Breakdown Voltage (I _C = 100 μAdc, I _E = 0)	V _{(BR)CBO}	140 175	— —	Vdc
		2N3634, 2N3635 2N3636, 2N3637		
Emitter-Base Breakdown Voltage (I _E = 10 μAdc, I _C = 0)	V _{(BR)EBO}	5.0	—	Vdc
Collector Cutoff Current (V _{CB} = 100 Vdc, I _E = 0)	I _{CBO}	—	100	nAdc
Emitter Cutoff Current (V _{BE} = 3.0 Vdc, I _C = 0)	I _{EBO}	—	50	nAdc
ON CHARACTERISTICS				
DC Current Gain(1) (I _C = 0.1 mAdc, V _{CE} = 10 Vdc)	h _{FE}	40 80	— —	—
		2N3634, 2N3636 2N3635, 2N3637		
(I _C = 1.0 mAdc, V _{CE} = 10 Vdc)		45 90	— —	
		2N3634, 2N3636 2N3635, 2N3637		
(I _C = 10 mAdc, V _{CE} = 10 Vdc)		50 100	— —	
		2N3634, 2N3636 2N3635, 2N3637		
(I _C = 50 mAdc, V _{CE} = 10 Vdc)		50 100	150 300	
		2N3634, 2N3636 2N3635, 2N3637		
(I _C = 150 mAdc, V _{CE} = 10 Vdc)		25 50	— —	
		2N3634, 2N3636 2N3635, 2N3637		
Collector-Emitter Saturation Voltage(1) (I _C = 10 mAdc, I _B = 1.0 mAdc) (I _C = 50 mAdc, I _B = 5.0 mAdc)	V _{CE(sat)}	— —	0.3 0.5	Vdc
		2N3634, 2N3636 2N3635, 2N3637		
Base-Emitter Saturation Voltage(1) (I _C = 10 mAdc, I _B = 1.0 mAdc) (I _C = 50 mAdc, I _B = 5.0 mAdc)	V _{BE(sat)}	— 0.65	0.8 0.9	Vdc
		2N3634, 2N3636 2N3635, 2N3637		
SMALL-SIGNAL CHARACTERISTICS				
Current-Gain — Bandwidth Product (V _{CE} = 30 Vdc, I _C = 30 mAdc, f = 100 MHz)	f _T	150 200	— —	MHz
		2N3634, 2N3636 2N3635, 2N3637		

2N3634 thru 2N3637

ELECTRICAL CHARACTERISTICS (continued) ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
Output Capacitance ($V_{CB} = 20\text{ Vdc}$, $I_E = 0$, $f = 100\text{ kHz}$)	C_{obo}	—	10	pF
Input Capacitance ($V_{BE} = 1.0\text{ Vdc}$, $I_C = 0$, $f = 100\text{ kHz}$)	C_{ibo}	—	75	pF
Input Impedance ($I_C = 10\text{ mAdc}$, $V_{CE} = 10\text{ Vdc}$, $f = 1.0\text{ kHz}$)	h_{ie}	100 200	600 1200	ohms
Voltage Feedback Ratio ($I_C = 10\text{ mAdc}$, $V_{CE} = 10\text{ Vdc}$, $f = 1.0\text{ kHz}$)	h_{re}	—	3.0	$\times 10^{-4}$
Small-Signal Current Gain ($I_C = 10\text{ mAdc}$, $V_{CE} = 10\text{ Vdc}$, $f = 1.0\text{ kHz}$)	h_{fe}	40 80	160 320	—
Output Admittance ($I_C = 10\text{ mAdc}$, $V_{CE} = 10\text{ Vdc}$, $f = 1.0\text{ kHz}$)	h_{oe}	—	200	μmhos
Noise Figure ($I_C = 0.5\text{ mAdc}$, $V_{CE} = 10\text{ Vdc}$, $R_S = 1.0\text{ k ohms}$, $f = 1.0\text{ kHz}$)	NF	—	3.0	dB

SWITCHING CHARACTERISTICS

Turn-On Time	($V_{CC} = 100\text{ Vdc}$, $V_{BE} = 4.0\text{ Vdc}$, $I_C = 50\text{ mAdc}$, $I_{B1} = I_{B2} = 5.0\text{ mAdc}$)	t_{on}	—	400	ns
Turn-Off Time		t_{off}	—	600	ns

(1) Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2.0\%$.

FIGURE 1 — JUNCTION CAPACITANCE VARIATIONS




FIGURE 2 — GAIN-BANDWIDTH PRODUCT





FIGURE 3 — CURRENT GAIN CHARACTERISTICS versus JUNCTION TEMPERATURE






FIGURE 4 — CURRENT GAIN CHARACTERISTICS versus COLLECTOR EMITTER VOLTAGE





FIGURE 5 — CURRENT GAIN CHARACTERISTICS versus JUNCTION TEMPERATURE



2N3634 thru 2N3637




FIGURE 6 — CURRENT GAIN CHARACTERISTICS versus COLLECTOR EMITTER VOLTAGE




FIGURE 7 — INPUT IMPEDANCE




FIGURE 8 — OUTPUT IMPEDANCE

FIGURE 9 — CURRENT GAIN




FIGURE 10 — VOLTAGE FEEDBACK RATIO




FIGURE 11 — SATURATION VOLTAGES




FIGURE 12 — TEMPERATURE COEFFICIENTS






FIGURE 13 — SWITCHING TIME TEST CIRCUIT



P.W. $\approx 20 \mu\text{s}$
 DUTY CYCLE $\leq 2\%$
 RISE TIME $\leq 20 \text{ ns}$

	V_{max}	V_{min}
TURN-ON	+4.0 V	-5.65 V
TURN-OFF	+4.1 V	-5.9 V



2N3634 thru 2N3637

FIGURE 14 — TURN-ON TIME VARIATIONS WITH VOLTAGE





FIGURE 15 — TURN-OFF TIME VARIATIONS WITH CIRCUIT GAIN*



2N3647, 2N3648

For Specifications, See 2N3510 Data.