

2N3993,A 2N3994,A

CASE 20-03, STYLE 5
TO-72 (TO-206AF)

JFET
SWITCHING

P-CHANNEL — DEPLETION

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	-25	Vdc
Drain-Gate Voltage	V _{DG}	-25	Vdc
Reverse Gate-Source Voltage	V _{GSR}	25	Vdc
Forward Gate Current	I _{GF}	10	mAdc
Total Device Dissipation @ T _A = 25°C Derate above 25°C	P _D	300 2.0	mW mW/°C
Storage Temperature Range	T _{stg}	-65 to +200	°C

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Gate-Source Breakdown Voltage (I _G = 1.0 μAdc, V _{DS} = 0)	V _{(BR)GSS}	25	—	Vdc
Drain Reverse Current (V _{DG} = -15 Vdc, I _S = 0) (V _{DG} = -15 Vdc, I _S = 0, T _A = 150°C)	I _{DGO}	— —	1.2 1.2	nAdc μAdc
Drain Cutoff Current (V _{DS} = -10 Vdc, V _{GS} = 10 Vdc) (V _{DS} = -10 Vdc, V _{GS} = 6.0 Vdc) (V _{DS} = -10 Vdc, V _{GS} = 10 Vdc, T _A = 150°) (V _{DS} = -10 Vdc, V _{GS} = 6.0 Vdc, T _A = 150°)	I _{D(off)}	— — — —	1.2 1.2 1.0 1.0	nAdc μAdc
Gate Source Voltage (V _{DS} = -10 Vdc, I _D = -1.0 μAdc)	V _{GS}	4.0 1.0	9.5 5.5	Vdc

ON CHARACTERISTICS

Zero-Gate-Voltage Drain Current(1) (V _{DS} = -10 Vdc, V _{GS} = 0)	2N3993, 2N3993A 2N3994, 2N3994A	I _{DSS}	10 2.0	— —	mAdc
--	------------------------------------	------------------	-----------	--------	------

SMALL-SIGNAL CHARACTERISTICS

Drain-Source "ON" Resistance (V _{GS} = 0, I _D = 0, f = 1.0 kHz)	2N3993, 2N3993A 2N3994, 2N3994A	r _{ds(on)}	— —	150 300	Ohms
Forward Transfer Admittance(1) (V _{DS} = -10 Vdc, V _{GS} = 0, f = 1.0 kHz)	2N3993 2N3993A 2N3994 2N3994A	Y _{fs}	6.0 7.0 4.0 5.0	12 12 10 10	mmhos
Input Capacitance (V _{DS} = -10 Vdc, V _{GS} = 0, f = 1.0 MHz)	2N3993, 2N3994 2N3993A, 2N3994A	C _{iss}	— —	16 12	pF
Reverse Transfer Capacitance (V _{DS} = 0, V _{GS} = 10 Vdc, f = 1.0 MHz)	2N3993 2N3993A	C _{rss}	— —	4.5 3.0	pF
(V _{DS} = 0, V _{GS} = 6.0 Vdc, f = 1.0 MHz)	2N3994 2N3994A		— —	5.0 3.5	

(1) Pulse Test: Pulse Width = 100 ms, Duty Cycle ≤ 10%.