


NPN Power Silicon Transistor

2N4150, 2N5237 & 2N5238



Features

- Available in JAN, JANTX, and JANTXV per MIL-PRF-19500/384
- TO-5 Package



Maximum Ratings

Ratings	Symbol	2N4150	2N5237	2N5238	Units
Collector - Emitter Voltage	V_{CEO}	70	120	170	Vdc
Collector - Base Voltage	V_{CBO}	100	150	200	Vdc
Emitter - Base Voltage	V_{EBO}	10.0			Vdc
Collector Current	I_C	4.0			Adc
Total Power Dissipation @ $T_A = +25^\circ\text{C}$ (1) @ $T_A = +25^\circ\text{C}$ (2)	P_T	10			W
		175			W
Operating & Storage Temperature Range	T_{op}, T_{stg}	-65 to +200			$^\circ\text{C}$
Thermal Resistance, Junction-to-Case Junction_to-Ambient	$R_{\theta JC}$	10.0			$^\circ\text{C/W}$
	$R_{\theta JA}$	175.0			

1) Derate linearly @ 5.7 mW/ $^\circ\text{C}$ for $T_A > +25^\circ\text{C}$

2) Derate linearly @ 100 mW/ $^\circ\text{C}$ for $T_C > +25^\circ\text{C}$

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

OFF Characteristics	Symbol	Mimumum	Maximum	Units
Collector - Emitter Breakdown Voltage $I_C = 0.1 \text{ mA}$	$V_{(BR)CEO}$	2N4150 70	---	Vdc
2N5237 120				
2N5238 170				
Collector - Emitter Cutoff Current $V_{BE} = 0.5 \text{ Vdc}, V_{CE} = 60 \text{ Vdc}$ $V_{BE} = 0.5 \text{ Vdc}, V_{CE} = 110 \text{ Vdc}$ $V_{BE} = 0.5 \text{ Vdc}, V_{CE} = 160 \text{ Vdc}$	I_{CEX}	2N4150 ---	10 10 10	μAdc
2N5237				
2N5238				
Collector - Emitter Cutoff Current $V_{CE} = 60 \text{ Vdc}$ $V_{CE} = 110 \text{ Vdc}$ $V_{CE} = 160 \text{ Vdc}$	I_{CEO}	2N4150 ---	10 10 10	μAdc
2N5237				
2N5238				
Emitter - Base Cutoff Current $V_{EB} = 7.0 \text{ Vdc}$ $V_{EB} = 5.0 \text{ Vdc}$	I_{EBO}	---	10	μAdc
0.1				
Collector-Base Cutoff Current $V_{CB} = 100 \text{ Vdc}$ $V_{CB} = 150 \text{ Vdc}$ $V_{CB} = 200 \text{ Vdc}$ $V_{CB} = 80 \text{ Vdc}$	I_{CBO}	2N4150 ---	10 10 10 0.1	μAdc
2N5237				
2N5238				
All Types				




Electrical Characteristics -con't

ON Characteristics		Symbol	Mimimum	Maximum	Units
Collector-Base Cutoff Current $I_C = 1.0 \text{ Adc}, V_{CE} = 5.0 \text{ Vdc}$	2N4150	H_{FE}	50	20	μAdc
	2N5237		50	225	
	2N5238		50	225	
$I_C = 5.0 \text{ Adc}, V_{CE} = 5.0 \text{ Vdc}$	All Types		40	120	
$I_C = 10.0 \text{ Adc}, V_{CE} = 5.0 \text{ Vdc}$	All Types		10	---	
Collector-Emitter Saturation Voltage $I_C = 5.0 \text{ Adc}, I_B = 0.5 \text{ Adc}$ $I_C = 10.0 \text{ Adc}, I_B = 1.0 \text{ Adc}$		$V_{CE(sat)}$	---	0.6 2.5	Vdc
Base-Emitter Saturation Voltage $I_C = 5.0 \text{ Adc}, I_B = 0.5 \text{ Adc}$ $I_C = 10.0 \text{ Adc}, I_B = 1.0 \text{ Adc}$		$V_{BE(sat)}$	---	1.5 25	Vdc
DYNAMIC Characteristics					
Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = 0.2 \text{ Adc}, V_{CE} = 10.0 \text{ Vdc}, f = 10 \text{ MHz}$		$ h_{fe} $	1.5	7.5	
Output Capacitance $I_C = 50 \text{ mVdc}, V_{CB} = 5.0 \text{ V}, f = 1.0 \text{ kHz}$	2N4150 2N5237 2N5238	C_{obo}	---	160 160 250	pF
Output Capacitance $V_{BE} = 10 \text{ Vdc}, I_E = 0, 100 \text{ kHz} \leq f \leq 1.0 \text{ MHz}$		C_{ibo}	---	350	pF
SWITCHING Characteristics					
Delay Time	$V_{CC} = 20 \text{ Vdc}, V_{BB} = 5.0 \text{ Vdc},$ $I_C = 5.0 \text{ Adc}, I_{B1} = 0.5 \text{ Adc}$	t_d	---	50	ns
Rise Time		t_r	---	500	ns
Storage Time	$V_{CC} = 20 \text{ Vdc}, V_{BB} = 5.0 \text{ Adc},$ $I_C = 5.0 \text{ Adc}, I_{B1} = -I_{B2} = -0.5 \text{ Adc}$	t_s	---	1.5	ns
Fall Time		t_f	---	500	ns
SAFE OPERATING AREA					
DC Tests:	$T_C = +25 \text{ }^\circ\text{C}, 1 \text{ Cycle}, t = 1.0 \text{ s}$				
Test 1:	$V_{CE} = 40.0 \text{ Vdc}, I_C = 0.22 \text{ Adc}$				
Test 2:	$V_{CE} = 70 \text{ Vdc}, I_C = 90 \text{ mAdc}$				
TEST 3:	$V_{CE} = 120 \text{ Vdc}, I_C = 15 \text{ mAdc}$	2N5237			
	$V_{CE} = 170 \text{ Vdc}, I_C = 3.5 \text{ mAdc}$	2N5238			

(1) Pulse Test: Pulse Width = 300 μs , Duty Cycle $\leq 2.0\%$.

Outline Drawing



Note: All dimensions are inches [mm].

Aeroflex / Metelics, Inc.

975 Stewart Drive,
Sunnyvale, CA 94085
Tel: (408) 737-8181
Fax: (408) 733-7645

Sales: 888-641-SEMI (7364)

Hi-Rel Components

9 Hampshire Street,
Lawrence, MA 01840
Tel: (603) 641-3800
Fax: (978) 683-3264

www.aeroflex.com/metelics-hirelcomponents

www.aeroflex.com/metelics metelics-sales@aeroflex.com

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2011 Aeroflex / Metelics. All rights reserved.

ISO 9001: 2008 certified companies



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.