

2N869A 2N4453

JAN, JTX, JTXV AVAILABLE

CASE 22-03, STYLE 1
TO-18 (TO-206AA)

2N4453
CASE 26-03, STYLE 1
TO-46 (TO-206AB)

SWITCHING TRANSISTOR

PNP SILICON

MAXIMUM RATINGS

Rating	Symbol	2N869A	2N4453	Unit
Collector-Emitter Voltage	V_{CEO}	18	18	Vdc
Collector-Emitter Voltage	V_{CES}	25		Vdc
Collector-Base Voltage	V_{CBO}	25*	25	Vdc
Emitter-Base Voltage	V_{EBO}	5.0		Vdc
Collector Current — Continuous	I_C	200		mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	360 2.06	400 2.29	mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ $T_C = 100^\circ\text{C}$ Derate above 25°C	P_D	1.2 0.686 6.86	2.0 1.03 11.3	Watts Watts mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200		$^\circ\text{C}$

THERMAL CHARACTERISTICS

Characteristic	Symbol	2N869A	2N4453	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	146	97.5	$^\circ\text{C/W}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	486	585	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage(1) ($I_C = 10\text{ mAdc}, I_B = 0$)	$V_{(BR)CEO}$	18	—	Vdc
Collector-Emitter Breakdown Voltage ($I_C = 10\text{ }\mu\text{Adc}, V_{BE} = 0$)	$V_{(BR)CES}$	25	—	Vdc
Collector-Emitter Sustaining Voltage(1) ($I_C = 10\text{ mAdc}, I_B = 0$)	$V_{CEO(sus)}$	18	—	Vdc
Collector-Base Breakdown Voltage ($I_C = 10\text{ }\mu\text{Adc}, I_E = 0$)	$V_{(BR)CBO}$	25	—	Vdc
Emitter-Base Breakdown Voltage ($I_E = 10\text{ }\mu\text{Adc}, I_C = 0$)	$V_{(BR)EBO}$	5.0	—	Vdc
Collector Cutoff Current ($V_{CB} = 15\text{ Vdc}, I_E = 0, T_A = 150^\circ\text{C}$)	I_{CBO}	—	25	μAdc
Collector Cutoff Current ($V_{CE} = 15\text{ Vdc}, V_{BE} = 0$)	I_{CES}	—	10	nAdc
Emitter Cutoff Current ($V_{EB} = 4.5\text{ Vdc}, I_C = 0$)	I_{EBO}	—	10	nAdc
Base Current ($V_{CE} = 15\text{ Vdc}, V_{BE} = 0$)	I_B	—	10	nAdc

ON CHARACTERISTICS(1)

DC Current Gain ($I_C = 10\text{ mAdc}, V_{CE} = 0.3\text{ Vdc}$) ($I_C = 10\text{ mAdc}, V_{CE} = 5.0\text{ Vdc}$) ($I_C = 30\text{ mAdc}, V_{CE} = 0.5\text{ Vdc}$) ($I_C = 30\text{ mAdc}, V_{CE} = 0.5\text{ Vdc}, T_A = -55^\circ\text{C}$) ($I_C = 100\text{ mAdc}, V_{CE} = 1.0\text{ Vdc}$)	2N869A 2N869A 2N869A, 2N4453 2N869A, 2N4453	h_{FE}	30 40 40 17 25	— 120 120 — —	—
Collector-Emitter Saturation Voltage ($I_C = 10\text{ mAdc}, I_B = 1.0\text{ mAdc}$) ($I_C = 30\text{ mAdc}, I_B = 1.5\text{ mAdc}$) ($I_C = 30\text{ mAdc}, I_B = 3.0\text{ mAdc}$) ($I_C = 100\text{ mAdc}, I_B = 10\text{ mAdc}$)	2N869A 2N4453 2N869A 2N869A, 2N4453	$V_{CE(sat)}$	— — — —	0.15 0.25 0.2 0.5	Vdc
Base-Emitter Saturation Voltage ($I_C = 10\text{ mAdc}, I_B = 1.0\text{ mAdc}$) ($I_C = 30\text{ mAdc}, I_B = 1.5\text{ mAdc}$) ($I_C = 30\text{ mAdc}, I_B = 3.0\text{ mAdc}$) ($I_C = 100\text{ mAdc}, I_B = 10\text{ mAdc}$)	2N869A 2N4453 2N869A 2N869A, 2N4453	$V_{BE(sat)}$	0.78 0.8 0.85 —	0.98 1.1 1.2 1.7	Vdc

2N869A, 2N4453

ELECTRICAL CHARACTERISTICS (continued) ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
SMALL-SIGNAL CHARACTERISTICS				
Current-Gain — Bandwidth Product(1)(2) ($I_C = 10\text{ mA}$, $V_{CE} = 15\text{ Vdc}$, $f = 100\text{ MHz}$)	f_T	400	—	MHz
Output Capacitance ($V_{CB} = 5.0\text{ Vdc}$, $I_E = 0$, $f = 140\text{ kHz}$)	C_{obo}	—	6.0	pF
Input Capacitance ($V_{BE} = 0.5\text{ Vdc}$, $I_C = 0$, $f = 150\text{ kHz}$)	C_{ibo}	—	6.0	pF
Collector-Base Capacitance ($V_{CB} = 5.0\text{ Vdc}$, $I_E = 0$, $f = 1.0\text{ MHz}$)	C_{cb}	—	6.0	pF
Emitter-Base Capacitance ($V_{BE} = 0.5\text{ Vdc}$, $I_C = 0$, $f = 1.0\text{ MHz}$)	C_{eb}	—	6.0	pF
SWITCHING CHARACTERISTICS				
Turn-On Time	t_{on}	—	50	ns
Delay Time	t_d	—	35	ns
Rise Time	t_r	—	20	ns
Turn-Off Time	t_{off}	—	80	ns
Storage Time	t_s	—	65	ns
Fall Time	t_f	—	20	ns

(1) Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle = 1.0%.

(2) f_T is defined as the frequency at which $|h_{fe}|$ extrapolates to unity.

TYPICAL SWITCHING CHARACTERISTICS

FIGURE 1 — SWITCHING TEST CIRCUIT VALUES

		V_{in} Volts	V_{BB} Volts	V_{CC} Volts	R_L Ohms	I_C mA	$I_{B1}^{(4)}$ mA	$I_{B2}^{(4)}$ mA
t_{on}, t_r, t_d	2N869A	-7.0	3.0	2.0	62	30	1.5	—
	2N4453	-7.0	3.0	3.0	91	30	1.5	—
t_{off}, t_s, t_f	2N869A	+6.0	-4.0	2.0	62	30	1.5	1.5
	2N4453	+6.0	-4.0	3.0	91	30	1.5	1.5

(3) $I_C/I_B = 10$. Switching is shown to reflect current industry practices. Compare the values shown in Figures 1 and 2 @ $I_C = 30\text{ mA}$ to the typical values in the Electrical Characteristics table @ $I_C/I_B = 20$.

(4) $I_{B1} = I_{B2} = 3.0\text{ mA}$ @ $I_C/I_B = 10$

FIGURE 2 — DC CURRENT GAIN





FIGURE 3 — "ON" VOLTAGES



2N869A, 2N4453

FIGURE 4 — CURRENT-GAIN — BANDWIDTH PRODUCT




FIGURE 5 — TURN-ON TIME




FIGURE 6 — TURN-OFF TIME




FIGURE 7 — SWITCHING TIME TEST CIRCUIT




FIGURE 8 — CAPACITANCE

