


isc Silicon NPN Power Transistors
2N5655
DESCRIPTION


- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 250V(\text{Min})$
- DC Current Gain-
: $h_{FE} = 30-250@I_C = 0.1A$
- Low Saturation Voltage
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for use in line-operated equipment such as audio output amplifiers; low-current, high-voltage converters; and AC line relays.


ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	275	V
V_{CEO}	Collector-Emitter Voltage	250	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	0.5	A
I_{CM}	Collector Current-Peak	1	A
I_B	Base Current	1	A
P_C	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	20	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$


THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	6.25	$^\circ\text{C/W}$

isc Silicon NPN Power Transistors
2N5655
ELECTRICAL CHARACTERISTICS

 T_C=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(SUS)}	Collector-Emitter Sustaining Voltage	I _C = 100mA ; L= 50mH	250			V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 1mA ; I _B = 0	250			V
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage	I _C = 0.1A; I _B = 10mA			1.0	V
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage	I _C = 0.25 A; I _B = 25mA			2.5	V
V _{CE(sat)-3}	Collector-Emitter Saturation Voltage	I _C = 0.5 A; I _B = 0.1A			10	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 0.1A ; V _{CE} = 10V			1.0	V
I _{CEO}	Collector Cutoff Current	V _{CE} = 150V; I _B = 0			0.1	mA
I _{CEX}	Collector Cutoff Current	V _{CE} =250V;V _{BE(off)} =1.5V V _{CE} =150V;V _{BE(off)} =1.5V,T _C =100°C			0.1 1.0	mA
I _{CBO}	Collector Cutoff Current	V _{CB} = 275V; I _E = 0			10	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 6V; I _C = 0			10	μ A
h _{FE-1}	DC Current Gain	I _C = 50mA ; V _{CE} = 10V	25			
h _{FE-2}	DC Current Gain	I _C = 0.1A ; V _{CE} = 10V	30		250	
h _{FE-3}	DC Current Gain	I _C = 0.25A ; V _{CE} = 10V	15			
h _{FE-4}	DC Current Gain	I _C = 0.5A ; V _{CE} = 10V	5			
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 10V; f= 100kHz			25	pF
f _T	Current-Gain—Bandwidth Product	I _C = 50mA; V _{CE} = 10V; f= 10MHz	10			MHz

Notice:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.