



keyword search:   part number search:

[Products](#)

[Support](#)

[Requests](#)

[Investors](#)

2N5730 (#23467)

[RFQ/Sample](#)

**NPN Transistor**

**Package**  
TO-59\_ISO(STD)

<b>Division</b>	<a href="#">Lawrence</a>	<b>Datasheet</b>	(none)
<b>Mil-Spec</b>	(none)		
<b>Shipping</b>	(none)	<b>Qual Data</b>	Contact Microsemi

Maximum Electrical Rating	Symbol	Max	Unit
<b>Power Dissipation</b>	<b>Power</b>	45	W
<b>Collector Current</b>	<b>I<sub>C</sub></b>	10	A
<b>Breakdown Voltage Collector-to-Base</b>	<b>B<sub>V(CBO)</sub></b>	100	V
<b>Voltage Collector to Emitter Open</b>	<b>V<sub>CEO</sub></b>	80	V
<b>Voltage Emitter to Base Open</b>	<b>BV<sub>EBO</sub></b>	5	V

Electrical Rating	Symbol	Min	Typ	Max	Unit
<b>Collector Emitter Saturation Voltage</b>				1.2	V
(I <sub>B</sub> =0.5 mA, I <sub>C</sub> =2 mA, T <sub>A</sub> =25 °C, 300µs pulse)	<b>V<sub>CE(sat)</sub></b>				
<b>DC Current Gain</b>				30	
(I <sub>C</sub> =2 mA, T <sub>A</sub> =25 °C, 300µs pulse)	<b>HFE</b>	30			

[Privacy Policy](#) | [Site Map](#)

[PPG Webex Portal](#) | [PPG Extranet Login](#)

[Avionics](#) | [Backlight Inverters](#) | [L-Band Radar](#) | [LED Driver](#) | [LDMOS & VDMOS](#) | [MOSFETs, IGBTs, & Diodes](#) | [Pin Diodes](#) | [Power Modules](#)  
[RF Power & Bipolar Transistors](#) | [S-Band Radar](#) | [SCR](#) | [Thyristors](#) | [Varacter Diode](#) | [WLAN Power Amplifier](#) | [Zener Diode](#) | [PoE](#) | [PoE ICs](#)

Copyright © 2007 Microsemi Corporation. All rights reserved