

Silicon PNP Power Transistors

2N5867 2N5868

DESCRIPTION

- With TO-3 package
- Low collector saturation voltage

APPLICATIONS

- For medium-speed switching and amplifier applications

PINNING

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings(Ta=□)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	2N5867	-60	V
		2N5868	-80	
V _{CEO}	Collector-emitter voltage	2N5867	-60	V
		2N5868	-80	
V _{EBO}	Emitter-base voltage	Open collector	-5	V
I _C	Collector current		-5	A
P _D	Total Power Dissipation	T _C =25□	87.5	W
T _j	Junction temperature		150	□
T _{stg}	Storage temperature		-65~200	□

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	VALUE	UNIT
R _{th j-c}	Thermal resistance junction to case	1.17	□/W

Silicon PNP Power Transistors

2N5867 2N5868

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	2N5867	I _C =-0.1A; I _B =0	-60			V
		2N5868		-80			
V _{CEsat}	Collector-emitter saturation voltage		I _C =-5A; I _B =-1A			-1.0	V
V _{BEsat}	Base-emitter saturation voltage		I _C =-5A; I _B =-1A			-1.5	V
I _{CBO}	Collector cut-off current		V _{CB} =ratedV _{CBO} ; I _B =0			-1.0	mA
I _{CEO}	Collector cut-off current	2N5867	V _{CE} =-30V; I _B =0			-2.0	mA
		2N5868	V _{CE} =-40V; I _B =0				
I _{EBO}	Emitter cut-off current		V _{EB} =-5V; I _C =0			-1.0	mA
h _{FE}	DC current gain		I _C =-1.5A; V _{CE} =-4V	20		100	
f _T	Transistion frequency		I _C =-0.5A; V _{CE} =-10V; f=1MHz	4			MHz

Silicon PNP Power Transistors

2N5867 2N5868

PACKAGE OUTLINE

