

isc Silicon PNP Power Transistor
2N6330
DESCRIPTION



- Collector-Emitter Breakdown Voltage-
: $V_{CEO} = -80V(\text{Min})$
- Minimum Lot-to-Lot variations for robust device
Performance and reliable operation

APPLICATIONS

- Power amplifier and switching applications

ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	-80	V
V_{CEO}	Collector-Emitter Voltage	-80	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current-Continuous	-30	A
P_D	Collector Power Dissipation @ $T_C = 25^\circ\text{C}$	200	W
T_J	Junction Temperature	-65~200	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~200	$^\circ\text{C}$



isc Silicon PNP Power Transistor

2N6330

ELECTRICAL CHARACTERISTICS

T_C=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C =-30mA	-80			V
I _{EBO}	Emitter-Base Cutoff Current	V _{BE} =-5V			-500	uA
I _{CEO}	Collector-Emitter Cutoff Current	V _{CE} = -40V			-1	mA
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage	I _C =-15A; I _B = -2A			-1.5	V
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage	I _C =-30A; I _B = -7.5A			-3	V
V _{BE(on)-1}	Base-Emitter On Voltage	I _C =-15A; V _{CE} =-4V			-2	V
V _{BE(on)-2}	Base-Emitter On Voltage	I _C =-30A; V _{CE} =4V			-4	V
h _{FE-1}	DC Current Gain	I _C =-5A; V _{CE} = -4V	25			
h _{FE-2}	DC Current Gain	I _C =-15A; V _{CE} = -4V	12			
h _{FE-3}	DC Current Gain	I _C =-30A; V _{CE} =-4V	6		30	

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.