

isc Silicon NPN Power Transistor
2N6545
DESCRIPTION

- Excellent Safe Operating Area
- High Voltage, High Speed
- Low Saturation Voltage
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Switching regulators
- PWM inverters and motor controls
- Solenoid and relay drivers
- Deflection circuits

ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CEV}	Collector-Emitter Voltage	850	V
$V_{CEO(SUS)}$	Collector-Emitter Voltage	400	V
V_{EBO}	Emitter-Base Voltage	9	V
I_C	Collector Current-Continuous	8	A
I_{CM}	Collector Current-Peak	16	A
I_B	Base Current-Continuous	8	A
P_C	Collector Power Dissipation@ $T_c=25^\circ\text{C}$	125	W
T_J	Junction Temperature	200	$^\circ\text{C}$
T_{stg}	Storage Temperature	-65~200	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.4	$^\circ\text{C}/\text{W}$



isc Silicon NPN Power Transistor

2N6545

ELECTRICAL CHARACTERISTICS

 $T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CEQ(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=50\text{mA}; I_B=0$	400		V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=5\text{A}; I_B=1.0\text{A}$		1.5	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=8\text{A}; I_B=2.0\text{A}$		5.0	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=5\text{A}; I_B=1.0\text{A}$		1.6	V
I_{EBO}	Emitter Cutoff Current	$V_{EB}=9\text{V}; I_C=0$		1.0	mA
I_{CBO}	Collector Base Cutoff Current	$V_{CB}=850\text{V}; I_E=0$		0.5	mA
h_{FE-1}	DC Current Gain	$I_C=2.5\text{A}; V_{CE}=3\text{V}$	12	60	
h_{FE-2}	DC Current Gain	$I_C=5\text{A}; V_{CE}=3\text{V}$	7	35	
f_T	Current Gain-Bandwidth Product	$I_C=0.3\text{A}; V_{CE}=10\text{V}; f_{test}=1.0\text{MHz}$	6.0		MHz

Switching times-Resistive Load

t_d	Delay Time	$I_C=5\text{A}, V_{CC}=250\text{V},$ $I_{B1}=-I_{B2}=1\text{A}, t_p=0.1\text{ms}$ Duty Cycle $\leq 2.0\%$		0.05	μs
t_r	Rise Time			1.0	μs
t_s	Storage Time			4.0	μs
t_f	Fall Time			1.0	μs

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.