

2N6547

SILICON NPN TRIPLE DIFFUSED TYPE

SWITCHING REGULATOR AND HIGH VOLTAGE
SWITCHING APPLICATIONS.
HIGH SPEED DC-DC CONVERTER, RELAY AND SOLENOID
DRIVER APPLICATIONS.


FEATURES:

- . High Sustaining Voltage : $V_{CEO(SUS)}=400V$ (Min.)
- . High Collector Current : $I_C=15A$ (Max.)
- . Excellent Switching Times

MAXIMUM RATINGS ($T_a=25^\circ C$)

CHARACTERISTIC		SYMBOL	RATING	UNIT	
Collector-Base Voltage		V_{CBO}	850	V	
*	Collector-Emitter Voltage	V_{CEV}	850	V	
*	Collector-Emitter Sustaining Voltage	$V_{CEX(SUS)}$	450	V	
*	Collector-Emitter Sustaining Voltage	$V_{CEO(SUS)}$	400	V	
Emitter-Base Voltage		V_{EBO}	9	V	
*	Collector Current	DC	I_C	15	A
		Peak	I_{CM}	30	A
Base Current		I_B	10	A	
Emitter Current		I_E	- 25	A	
*	Collector Power Dissipation	$T_c=25^\circ C$	P_C	175	W
		$T_c=100^\circ C$		100	W
Derate Linearly above $25^\circ C$			1	W/ $^\circ C$	
Junction Temperature		T_j	200	$^\circ C$	
Storage Temperature Range		T_{stg}	-65 ~ 200	$^\circ C$	
Thermal Resistance		θ_{jc}	1	$^\circ C/W$	
Lead Temperature (3.17mm from case for 5s)		T_L	275	$^\circ C$	

Unit in mm



Weight : 15.8g

ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT			
* Collector Cut-off Current	ICEV	VCE=850V, VBE=-1.5V	-	-	1	mA			
* Collector Cut-off Current	ICEV	VCE=850V, VBE=-1.5V, Tc=100°C	-	-	4	mA			
* Collector Cut-off Current	ICER	VCE=850V, RBE=50Ω, Tc=100°C	-	-	5	mA			
* Emitter Cut-off Current	IEBO	VEB=9V, IC=0	-	-	1	mA			
* Collector-Emitter Sustaining Voltage (Note:1)	VCEX(SUS)**	IC=8A, Vclamp=450V, Tc=100°C	450	-	-	V			
		IC=15A, Vclamp=300V, Tc=100°C	300	-	-	V			
* Collector-Emitter Sustaining Voltage	VCEO(SUS)**	IC=0.1A, IB=0	400	-	-	V			
* DC Current Gain	hFE	VCE=2V, IC=5A	12	-	60				
		VCE=2V, IC=10A	6	-	30				
* Collector-Emitter Saturation Voltage	VCE(sat)	IC=10A, IB=2A	-	-	1.5	V			
		IC=15A, IB=3A	-	-	5	V			
		IC=10A, IB=2A, Tc=100°C	-	-	2.5	V			
* Base-Emitter Saturation Voltage	VBE(sat)	IC=10A, IB=2A	-	-	1.6	V			
		IC=10A, IB=2A, Tc=100°C	-	-	1.6	V			
* Transition Frequency	fT	VCE=10V, IC=0.5A, f=1MHz	6	-	28	MHz			
* Collector Output Capacitance	Cob	VCB=10V, IE=0, f=1MHz	125	-	500	pF			
* Switching Time	Delay Time	td			-	-	0.05	µs	
	Rise Time	tr			-	-	1.0	µs	
	Storage Time	tstg			-	-	4.0	µs	
	Fall Time	tf			-	-	0.7	µs	
	Storage Time	tstg			See Fig.1	-	-	5.0	µs
	Fall Time	tf			Tc=100°C	-	-	1.5	µs
* Second Breakdown Collector Current (Base forward biased)	IS/b	VCE=100V, t=1s (non repetitive)	0.2	-	-	A			

* In Accordance with JEDEC Registration Data.

** The sustaining voltages VCEX(SUS) and VCEO(SUS) MUST NOT be measured on a curve tracer.

Note.1 : Test condition VCC=20V, L=180µH (LR=0.05Ω)

Fig. 1 : Inductive Load Switching Time Test Circuit

