

isc Silicon NPN Power Transistor
2N6574
DESCRIPTION



- Collector-Emitter Sustaining Voltage-
: $V_{CEO} = 275V(\text{Min.})$
- Fast Switching Speed
- High Current Capability
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for converters, inverters, pulse-width- modulated regulators and a variety of power switching circuits.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	600	V
V_{CEO}	Collector-Emitter Voltage	275	V
V_{EBO}	Emitter-Base Voltage	5	V
I_c	Collector Current-Continuous	10	A
P_C	Collector Power Dissipation@ $T_c=25^\circ\text{C}$	125	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature	-65~150	$^\circ\text{C}$



isc Silicon NPN Power Transistor

2N6574

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=3A; I_B=0.3A$		1	V
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C=7A; V_{CE}=3V$		1.4	V
I_{EBO}	Emitter Cutoff Current	$V_{EB}=8V; I_C=0$		0.1	mA
I_{CBO}	Collector Base Cutoff Current	$V_{CB}=600V; I_E=0$		0.1	mA
h_{FE-1}	DC Current Gain	$I_C=3A; V_{CE}=3V$	20	60	
h_{FE-2}	DC Current Gain	$I_C=7A; V_{CE}=3V$	7	21	
f_T	Current Gain-Bandwidth Product	$I_C=1A; V_{CE}=10V$	5		MHz
Switching times					
T_{on}	On Time	$I_C=7A; I_B=1.4A,$		1	μs
t_{off}	Off Time			3.2	μs

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.