

2N735 (SILICON)

2N736

2N739

2N740



NPN silicon annular transistors designed for small-signal amplifier and general purpose switching applications.

CASE 22
(TO-18)

Collector connected to case

MAXIMUM RATINGS

Rating	Symbol	2N735	2N739	Unit
		2N736	2N740	
Collector-Emitter Voltage	V_{CEO}	60	80	Vdc
Collector-Base Voltage	V_{CB}	80	125	Vdc
Emitter-Base Voltage	V_{EB}	5.0		Vdc
Collector Current	I_C	1.0		Adc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	500		mW
		2.86		mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to +200		$^\circ\text{C}$

Lead Temperature, $1/16'' \pm 1/32''$ from case for 10 s.

2N735, 2N736, 2N739, 2N740 (Continued)

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage ⁽¹⁾ ($I_C = 10\text{ mAdc}$, $I_B = 0$)	2N735, 2N736 2N739, 2N740	BV_{CEO}	60 80	- -	Vdc
Collector-Base Breakdown Voltage ($I_C = 10\ \mu\text{Adc}$, $I_E = 0$)	2N735, 2N736 2N739, 2N740	BV_{CBO}	80 125	- -	Vdc
Emitter-Base Breakdown Voltage ($I_E = 10\ \mu\text{Adc}$, $I_C = 0$)		BV_{EBO}	5.0	-	Vdc
Collector Cutoff Current ($V_{CB} = 40\text{ Vdc}$, $I_E = 0$)		I_{CBO}	-	1.0	μAdc
Emitter Cutoff Current ($V_{BE} = 5.0\text{ Vdc}$, $I_C = 0$)		I_{EBO}	-	10	μAdc

ON CHARACTERISTICS

DC Current Gain ($I_C = 5.0\text{ mAdc}$, $V_{CE} = 5.0\text{ Vdc}$)	2N735, 2N739 2N736, 2N740	h_{FE}	30 60	100 200	-
Collector-Emitter Saturation Voltage ($I_C = 10\text{ mAdc}$, $I_B = 2.0\text{ mAdc}$)		$V_{CE(sat)}$	-	1.0	Vdc
Base-Emitter Voltage ($I_C = 10\text{ mAdc}$, $I_B = 2.0\text{ mAdc}$)		V_{BE}	0.35	1.5	Vdc

SMALL-SIGNAL CHARACTERISTICS

Output Capacitance ($V_{CB} = 5.0\text{ Vdc}$, $I_E = 0$, $f = 1.0\text{ MHz}$)		C_{ob}	-	10	pF
Input Impedance ($I_C = 5.0\text{ mAdc}$, $V_{CE} = 5.0\text{ Vdc}$, $f = 1.0\text{ kHz}$)	2N735, 2N739 2N736, 2N740	h_{ie}	- -	1500 1800	Ohm
Small-Signal Current Gain ($I_C = 5.0\text{ mAdc}$, $V_{CE} = 5.0\text{ Vdc}$, $f = 1.0\text{ Hz}$)	2N735, 2N739 2N736, 2N740	h_{fe}	40 80	100 200	-

⁽¹⁾ Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2.0\%$.