

Silicon PNP Power Transistors

2SB1022

DESCRIPTION


- With TO-220Fa package
- High DC current gain
- Low saturation voltage
- Complement to type 2SD1417

APPLICATIONS

- High power switching applications
- Hammer drive,pulse motor drive applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter

Absolute maximum ratings($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-60	V
V_{CEO}	Collector -emitter voltage	Open base	-60	V
V_{EBO}	Emitter-base voltage	Open collector	-5	V
I_C	Collector current		-7	A
I_B	Base current		-0.2	A
P_C	Collector power dissipation	$T_a=25^\circ\text{C}$	2.0	W
		$T_C=25^\circ\text{C}$	30	
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~150	$^\circ\text{C}$

Silicon PNP Power Transistors

2SB1022

CHARACTERISTICS

Tj=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=-50mA; I_B=0$	-60			V
$V_{CEsat-1}$	Collector-emitter saturation voltage	$I_C=-3A; I_B=-6mA$			-1.5	V
$V_{CEsat-2}$	Collector-emitter saturation voltage	$I_C=-7A; I_B=-14mA$			-2.0	V
V_{BEsat}	Base-emitter saturation voltage	$I_C=-3A; I_B=-6mA$			-2.5	V
I_{CBO}	Collector cut-off current	$V_{CB}=-60V; I_E=0$			-100	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=-5V; I_C=0$			-4.0	mA
h_{FE-1}	DC current gain	$I_C=-3A; V_{CE}=-3V$	2000		15000	
h_{FE-2}	DC current gain	$I_C=-7A; V_{CE}=-3V$	1000			


Switching times

t_{on}	Turn-on time	$I_{B1}=-I_{B2}=-6mA; V_{CC}\approx-45V$ $R_L=15\Omega$		0.8		μs
t_{stg}	Storage time			2.0		μs
t_f	Fall time			2.5		μs

Silicon PNP Power Transistors

2SB1022

PACKAGE OUTLINE

Fig.2 Outline dimensions (unindicated tolerance: ± 0.15 mm)