

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free


## FEATURES

- General Purpose Switching and Amplification.

## TO-92


## CLASSIFICATION OF $h_{FE}$

Product-Rank	2SC1008-R	2SC1008-Q	2SC1008-Y	2SC1008-G
Range	40~80	70~140	120~240	200~400



① Emitter  
② Base  
③ Collector

REF.	Millimeter	
	Min.	Max.
A	4.40	4.70
B	4.30	4.70
C	12.70	-
D	3.30	3.81
E	0.36	0.56
F	0.36	0.51
G	1.27 TYP.	
H	1.10	-
J	2.42	2.66
K	0.36	0.76



## ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	80	V
Collector to Emitter Voltage	$V_{CEO}$	60	V
Emitter to Base Voltage	$V_{EBO}$	8	V
Collector Current - Continuous	$I_C$	0.7	A
Collector Power Dissipation	$P_C$	800	mW
Thermal Resistance From Junction to Ambient	$R_{\theta JA}$	156	$^\circ\text{C} / \text{W}$
Junction, Storage Temperature	$T_J, T_{STG}$	150, -55~150	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test condition
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	80	-	-	V	$I_C=0.1\text{mA}, I_E=0$
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	60	-	-	V	$I_C=10\text{mA}, I_B=0$
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	8	-	-	V	$I_E=0.01\text{mA}, I_C=0$
Collector Cut-Off Current	$I_{CBO}$	-	-	0.1	$\mu\text{A}$	$V_{CB}=60\text{V}, I_E=0$
Emitter Cut-Off Current	$I_{EBO}$	-	-	0.1	$\mu\text{A}$	$V_{EB}=5\text{V}, I_C=0$
DC Current Gain	$h_{FE}$	40	-	400		$V_{CE}=2\text{V}, I_C=50\text{mA}$
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	-	-	0.4	V	$I_C=500\text{mA}, I_B=50\text{mA}$
Base to Emitter Voltage	$V_{BE(sat)}$	-	-	1.1	V	$I_C=500\text{mA}, I_B=50\text{mA}$
Transition Frequency	$f_T$	30	-	-	MHz	$V_{CE}=10\text{V}, I_C=50\text{mA}$
Collector Output Capacitance	$C_{ob}$	-	8	-	pF	$V_{CB}=10\text{V}, I_C=0, f=1\text{MHz}$