

isc Silicon NPN Power Transistor
2SC1173
DESCRIPTION

- Low Collector Saturation Voltage
- Complement to Type 2SA473
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Power amplifier applications
- Car radio, car stereo output stage amplifier applications.

ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	30	V
V _{CEO}	Collector-Emitter Voltage	30	V
V _{EBO}	Emitter-Base Voltage	5	V
I _C	Collector Current-Continuous	3	A
P _C	Total Power Dissipation @ T _C =25°C	10	W
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-55~150	°C

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	12.5	°C/W



isc Silicon NPN Power Transistor
2SC1173
ELECTRICAL CHARACTERISTICS

 T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 10mA ; I _B = 0	30			V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	I _C = 1mA ; I _E = 0	30			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 1mA ; I _C = 0	5			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 2A; I _B = 0.2A			0.8	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 0.5A ; V _{CE} = 2V			1.0	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 20V ; I _E = 0			1.0	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0			1.0	μ A
h _{FE-1}	DC Current Gain	I _C = 0.5A ; V _{CE} = 2V	70		240	
h _{FE-2}	DC Current Gain	I _C = 2.5A ; V _{CE} = 2V	25			
f _T	Current-Gain—Bandwidth Product	I _C = 0.5A; V _{CE} = 2V; f _{test} = 1MHz		100		MHz

◆ h_{FE-1} Classifications

O	Y
70-140	120-240

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.