


isc Silicon NPN Power Transistor
2SC1618
DESCRIPTION


- High voltage
- Wide area of safe operation
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for audio frequency output applications


ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	80	V
V _{CEO}	Collector-Emitter Voltage	60	V
V _{EBO}	Emitter-Base Voltage	6	V
I _C	Collector Current-Continuous	6	A
P _C	Collector Power Dissipation	50	W
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-55~150	°C


THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	2.5	°C/W

isc Silicon NPN Power Transistor

2SC1618

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _c =4A; I _B = 0.4A			2.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _c =4A; I _B = 0.4A			2.5	V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _c = 25mA; I _B = 0	60			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 1mA; I _C = 0	6			V
h _{FE}	DC Current Gain	I _c =3A; V _{CE} = 4V	20		180	
I _{CB0}	Collector Cutoff Current	V _{CB} = 80V; I _E = 0			0.1	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 6V; I _C = 0			0.1	mA

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.