


27MHz POWER AMPLIFIER APPLICATIONS.

FEATURES:

- Recommended for Output Stage Application of AM 4W Transmitter.
- High Power Gain.
- Wide Area of Safe Operation.

MAXIMUM RATINGS (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V _{CB0}	80	V
Collector-Emitter Voltage R _{BE} =50Ω	V _{CER}	80	V
Emitter-Base Voltage	V _{EBO}	4.0	V
Collector Current	I _C	4	A
Emitter Current	I _E	-4	A
Collector Power Dissipation (Tc=25°C)	P _C	10	W
Junction Temperature	T _j	150	°C
Storage Temperature Range	T _{stg}	-55~150	°C




Mounting Kit No. AC75
Weight : 1.9g

ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		I _{CB0}	V _{CB} =30V, I _E =0	-	-	10	μA
Breakdown Voltage	Collector-Emitter	V _{(BR)CER}	I _C =10mA, R _{BE} =50Ω	80	-	-	V
	Emitter-Base	V _{(BR)EBO}	I _E =1.0mA, I _C =0	4.0	-	-	V
DC Current Gain		h _{FE} (1)	V _{CE} =5V, I _C =0.5A	25	-	-	
		h _{FE} (2)	V _{CE} =2V, I _C =3A	15	-	-	
Collector-Emitter Saturation Voltage		V _{CE(sat)}	I _C =3A, I _B =0.3A	-	-	1.5	V
Transition Frequency		f _T	V _{CE} =5V, I _C =500mA	-	100	-	MHz
Collector Output Capacitance		C _{ob}	V _{CB} =10V, I _E =0, f=1MHz	-	40	-	pF
Output Power (Fig. 1)		P _o	V _{CC} =12V, P _i =0.3W, f=27MHz	3.5	-	-	W

Fig.1 P_o TEST CIRCUIT



- C₁ : ~100pF, C₂, C₃ : ~150pF, C₄ : ~300pF, C₅ : 1000pF
 C₆ : 0.01μF R : 250Ω
 L₁ : 0.8mm∅ UEW, 7T, 8mm I.D L₂ : 0.8mm∅ UEW, 5T, 8mm I.D
 L₃ : 0.8mm∅ UEW, 10T, 8mm I.D RFC : 0.35mm∅ UEW, 17T, 5mm I.D

2SC2075










FIG. 2 27MHz 4W OUTPUT AM TRANSCEIVER CIRCUIT



L₁ : 4mm ϕ BOBBIN WITH FERRITE CORE , 0.08mm ϕ UEW, 8 TURNS

L₂ : 4mm ϕ BOBBIN WITH FERRITE CORE , 0.08mm ϕ UEW, 2 TURNS

L₃, L₆ : 6.5mm ϕ BOBBIN WITH FERRITE CORE , 0.6mm ϕ Sn PLATED COPPER WIRE 6 $\frac{1}{2}$ TURNS

L₄ : 6.5mm ϕ BOBBIN WITH FERRITE CORE , 0.6mm ϕ Sn PLATED COPPER WIRE 8 $\frac{1}{2}$ TURNS

L₅ : 0.6mm ϕ Sn PLATED COPPER WIRE , 6.5mm I.D., 8 $\frac{1}{2}$ TURNS

RFC₁ : 47 μ H, 7BA - 480k (TOKO)

RFC₂ : 0.2mm ϕ UEW, 50 TURNS

RESISTOR : $\frac{1}{4}$ W CARBON

CAPACITOR : CERAMIC

APPLICATION CIRCUIT CHARACTERISTIC

