

RoHS Compliant Product

A suffix of "-C" specifies halogen & lead-free



FEATURES

- High DC Current Gain
- Complementary to 2SA950

CLASSIFICATION OF h_{FE}

Product-Rank	2SC2120-O	2SC2120-Y
Range	100~200	160~320

TO-92



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CB0}	35	V
Collector to Emitter Voltage	V_{CEO}	30	V
Emitter to Base Voltage	V_{EBO}	5	V
Collector Current - Continuous	I_C	0.8	A
Collector Power Dissipation	P_C	0.6	W
Thermal Resistance From Junction to Ambient	$R_{\theta JA}$	208	$^\circ\text{C} / \text{W}$
Junction, Storage Temperature	T_J, T_{STG}	150, -55~150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Collector to Base Breakdown Voltage	$V_{(BR)CB0}$	35	-	-	V	$I_C=0.1\text{mA}, I_E=0$
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	30	-	-	V	$I_C=10\text{mA}, I_B=0$
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	5	-	-	V	$I_E=0.1\text{mA}, I_C=0$
Collector Cut - Off Current	I_{CB0}	-	-	0.1	μA	$V_{CB}=35\text{V}, I_E=0$
Collector Cut - Off Current	I_{CEO}	-	-	0.1	μA	$V_{CE}=25\text{V}, I_B=0$
Emitter Cut - Off Current	I_{EBO}	-	-	0.1	μA	$V_{EB}=5\text{V}, I_C=0$
DC Current Gain	h_{FE}	100	-	320		$V_{CE}=1\text{V}, I_C=100\text{mA}$
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	-	-	0.5	V	$I_C=500\text{mA}, I_B=20\text{mA}$
Base to Emitter voltage	V_{BE}	-	-	0.8	V	$V_{CE}=1\text{V}, I_C=10\text{mA}$
Collector Output Capacitance	C_{ob}	-	-	13	pF	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$
Transition Frequency	f_T	100	-	-	MHz	$V_{CE}=5\text{V}, I_C=10\text{mA}$

CHARACTERISTIC CURVES

