

**isc Silicon NPN Power Transistor**
**2SC2137**
**DESCRIPTION**



- High Collector-Emitter Breakdown Voltage-  
:  $V_{(BR)CEO} = 400V$  (Min)
- High Switching Speed
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**

- Switching regulator and high voltage switching applications.
- High speed DC-DC converter applications.

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ C$ )**

SYMBOL	PARAMETER	MAX	UNIT
$V_{CBO}$	Collector-Base Voltage	500	V
$V_{CEO}$	Collector-Emitter Voltage	400	V
$V_{EBO}$	Emitter-Base Voltage	6	V
$I_C$	Collector Current-Continuous	7	A
$I_B$	Base Current-Continuous	2	A
$P_C$	Collector Power Dissipation @ $T_c=25^\circ C$	80	W
$T_j$	Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ C$



**isc Silicon NPN Power Transistor****2SC2137****ELECTRICAL CHARACTERISTICS** $T_C=25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	$I_C = 10\text{mA}; I_B = 0$	400			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	$I_C = 1\text{mA}; I_E = 0$	500			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E = 1\text{mA}; I_C = 0$	6			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 3\text{A}; I_B = 0.3\text{A}$			1.5	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = 3\text{A}; I_B = 0.3\text{A}$			2.0	V
$h_{FE}$	DC Current Gain	$I_C = 3\text{A}; V_{CE} = 5\text{V}$	10			
$I_{CBO}$	Collector Cutoff Current	$V_{CB} = 400\text{V}; I_E = 0$			0.1	mA
$I_{EBO}$	Emitter Cutoff Current	$V_{EB} = 6\text{V}; I_C = 0$			1.0	mA

## Switching Times

$t_r$	Rise Time	$V_{CC} = 200\text{V}; I_{B1} = -I_{B2} = 0.3\text{A}; R_L = 40\ \Omega$			1.0	$\mu\text{s}$
$t_{stg}$	Storage Time				2.0	$\mu\text{s}$
$t_f$	Fall Time				1.0	$\mu\text{s}$

---

**isc Silicon NPN Power Transistor****2SC2137**

---

**Notice:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

