


POWER AMPLIFIER APPLICATIONS.

FEATURES:

- Suitable for TV Sound Output, Vert. Deflection Output.
- Designed for Complementary Use with 2SA962A.

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	60	V
Collector-Emitter Voltage	V_{CEO}	50	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current	I_C	1.5	A
Emitter Current	I_E	-1.5	A
Collector Power Dissipation	P_C	1.5	W
Junction Temperature	T_j	150	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-55 ~ 150	$^{\circ}\text{C}$



Weight : 1.37g

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=50\text{V}$, $I_E=0$	-	-	1.0	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=5\text{V}$, $I_C=0$	-	-	1.0	μA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=10\text{mA}$, $I_B=0$	50	-	-	V
DC Current Gain	h_{FE}	$V_{CE}=2\text{V}$, $I_C=150\text{mA}$	70	-	240	
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$	$I_C=1\text{A}$, $I_B=0.1\text{A}$	-	-	1.0	V
Base-Emitter Voltage	V_{BE}	$V_{CE}=10\text{V}$, $I_C=10\text{mA}$	0.50	0.60	0.70	V
Transition Frequency	f_T	$V_{CE}=10\text{V}$, $I_C=100\text{mA}$	50	100	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{V}$, $I_E=0$, $f=1\text{MHz}$	-	20	-	pF

2SC2194A

