

HIGH CURRENT SWITCHING APPLICATIONS.

INDUSTRIAL APPLICATIONS


Unit in mm

FEATURES:

- Low Collector Saturation Voltage
: $V_{CE(sat)} = 0.4V(\text{Max.})$ at $I_C = 3A$
- High Speed Switching Time : $t_{stg} = 1.0\mu s(\text{Typ.})$
- Complementary to 2SA1293.

MAXIMUM RATINGS ($T_a = 25^\circ C$)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CBO}	100	V
Collector-Emitter Voltage		V_{CEO}	80	V
Emitter-Base Voltage		V_{EBO}	7	V
Collector Current	DC	I_C	5	A
	Pulse	I_{CP}	8	
Collector Power Dissipation ($T_c = 25^\circ C$)		P_C	30	W
Junction Temperature		T_j	150	$^\circ C$
Storage Temperature Range		T_{stg}	-55 ~ 150	$^\circ C$

ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ C$)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		I_{CBO}	$V_{CB} = 100V, I_E = 0$	-	-	1	μA
Emitter Cut-off Current		I_{EBO}	$V_{EB} = 7V, I_C = 0$	-	-	1	μA
Collector-Emitter Breakdown Voltage		$V_{(BR)CEO}$	$I_C = 10mA, I_B = 0$	80	-	-	V
DC Current Gain		$h_{FE(1)}$ (Note)	$V_{CE} = 1V, I_C = 1A$	70	-	240	
		$h_{FE(2)}$	$V_{CE} = 1V, I_C = 3A$	40	-	-	
Saturation Voltage	Collector-Emitter	$V_{CE(sat)}$	$I_C = 3A, I_B = 0.15A$	-	0.2	0.4	V
	Base-Emitter	$V_{BE(sat)}$		-	0.9	1.2	
Transition Frequency		f_T	$V_{CE} = 4V, I_C = 1A$	-	120	-	MHz
Collector Output Capacitance		C_{ob}	$V_{CB} = 10V, I_E = 0, f = 1MHz$	-	80	-	pF
Switching Time	Turn-on Time	t_{on}		-	0.2	-	μs
	Storage Time	t_{stg}		-	1.0	-	
	Fall Time	t_f		-	0.1	-	

Note : $h_{FE(1)}$ Classification 0 : 70 ~ 140, Y : 120 ~ 240

TOSHIBA CORPORATION

