


**isc Silicon NPN Power Transistor**
**2SC3465**
**DESCRIPTION**


- High Breakdown Voltage-  
:  $V_{(BR)CBO} = 1100V(\text{Min})$
- Fast Switching Speed
- Wide Area of Safe Operation
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**

- Designed for switching regulator Applications


**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	1100	V
$V_{CEO}$	Collector-Emitter Voltage	800	V
$V_{EBO}$	Emitter-Base Voltage	7	V
$I_C$	Collector Current-Continuous	12	A
$I_{CM}$	Collector Current-Peak	30	A
$I_B$	Base Current-Continuous	6	A
$P_C$	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	160	W
$T_J$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55~150	$^\circ\text{C}$



**isc Silicon NPN Power Transistor**
**2SC3465**
**ELECTRICAL CHARACTERISTICS**

 T<sub>C</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage	I <sub>C</sub> = 5mA; R <sub>BE</sub> = ∞	800			V
V <sub>CEO(SUS)</sub>	Collector-Emitter Sustaining Voltage	I <sub>C</sub> = 6A; I <sub>B1</sub> = -I <sub>B2</sub> = 1.2A; L= 1mH; clamped	800			V
V <sub>(BR)CBO</sub>	Collector-Base Breakdown Voltage	I <sub>C</sub> = 1mA; I <sub>E</sub> = 0	1100			V
V <sub>(BR)EBO</sub>	Emitter-Base Breakdown Voltage	I <sub>E</sub> = 1mA; I <sub>C</sub> = 0	7			V
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 6A; I <sub>B</sub> = 1.2A			2.0	V
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage	I <sub>C</sub> = 6A; I <sub>B</sub> = 1.2A			1.5	V
I <sub>CBO</sub>	Collector Cutoff Current	V <sub>CB</sub> = 800V; I <sub>E</sub> =0			10	μ A
I <sub>EBO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = 5V; I <sub>C</sub> =0			10	μ A
h <sub>FE-1</sub>	DC Current Gain	I <sub>C</sub> = 0.8A; V <sub>CE</sub> = 5V	10		40	
h <sub>FE-2</sub>	DC Current Gain	I <sub>C</sub> = 4A; V <sub>CE</sub> = 5V	8			
C <sub>OB</sub>	Output Capacitance	I <sub>E</sub> = 0; V <sub>CB</sub> = 10V; f <sub>test</sub> =1.0MHz		240		pF
f <sub>T</sub>	Current-Gain—Bandwidth Product	I <sub>C</sub> = 0.8A; V <sub>CE</sub> = 10V		15		MHz
Switching times						
t <sub>on</sub>	Turn-on Time	I <sub>C</sub> = 8A, I <sub>B1</sub> = 1.6A; I <sub>B2</sub> = -3.2A R <sub>L</sub> = 50 Ω; V <sub>CC</sub> =400V			0.5	μ s
t <sub>stg</sub>	Storage Time				3.0	μ s
t <sub>f</sub>	Fall Time				0.3	μ s

**◆ h<sub>FE-1</sub> Classifications**

K	L	M
10-20	15-30	20-40

**Notice:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.