

SHINDENGEN


Switching Power Transistor

FX Series

2SC4051
(T3V45FX)

3A NPN

OUTLINE DIMENSIONS



RATINGS

Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T _{stg}		-55 ~ 150	
Junction Temperature	T _j		150	
Collector to Base Voltage	V _{CB0}		600	V
Collector to Emitter Voltage	V _{CEO}		450	V
	V _{CEx}	V _{EB} = 5V	600	
Emitter to Base Voltage	V _{EBO}		7	V
Collector Current DC	I _C		3	A
Collector Current Peak	I _{CP}		6	
Base Current DC	I _B		1	A
Base Current Peak	I _{BP}		2	
Total Transistor Dissipation	P _T	T _c = 25	40	W
Mounting Torque	TOR		0.5	N·m

Electrical Characteristics (T_c=25)


Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	V _{CEO(sus)}	I _C = 0.1A	Min 450	V
Collector Cutoff Current	I _{CB0}	At rated Voltage	Max 0.1	
	I _{CEO}		Max 0.1	
Emitter Cutoff Current	I _{EBO}	At rated Voltage	Max 0.1	mA
DC Current Gain	h _{FE}	V _{CE} = 5V, I _C = 1.5A	Min 10	
	h _{FEL}	V _{CE} = 5V, I _C = 1mA	Min 5	
Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C = 1.5A	Max 1.0	V
Base to Emitter Saturation Voltage	V _{BE(sat)}	I _B = 0.3A	Max 1.5	
Thermal Resistance	θ _{JC}	Junction to case	Max 3.12	/W
Transition Frequency	f _T	V _{CE} = 10V, I _C = 0.3A	STD 20	MHz
Turn on Time	t _{on}	I _C = 1.5A	Max 0.5	μs
Storage Time	t _s	I _{B1} = 0.3A, I _{B2} = 0.6A	Max 2.0	
Fall Time	t _f	R _L = 100 Ω, V _{BB2} = 4V	Max 0.2	

2SC4051

$h_{FE} - I_c$




2SC4051 Saturation Voltage




2SC4051

Switching Time - I_C




2SC4051 Switching Time - V_{CC}




2SC4051


Switching Time - Tc




2SC4051 L-Load Switching Time - I_C




2SC4051 L-Load Switching Time - I_C (At High Temperature)



2SC4051 Transient Thermal Impedance



2SC4051 Forward Bias SOA



2SC4051 Collector Current Derating



2SC4051

Reverse Bias SOA

