


isc Silicon NPN Power Transistor
2SC4370
DESCRIPTION


- High Collector-Emitter Breakdown Voltage
 $V_{CE0} = 160V(\text{Min})$
- Complement to Type 2SA1659
- Full-mold package that does not require an insulating board or bushing when mounting.
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


APPLICATIONS

- Designed for high voltage applications

ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	160	V
V_{CEO}	Collector-Emitter Voltage	160	V
V_{EBO}	Emitter-Base Voltage	5.0	V
$I_{C(DC)}$	Collector Current(DC)	1.5	A
$I_{B(DC)}$	Base Current	0.15	A
P_C	Collector Power Dissipation $@T_c = 25^\circ\text{C}$	20	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature	-55~150	$^\circ\text{C}$



isc Silicon NPN Power Transistor

2SC4370

ELECTRICAL CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 10mA ; I _B = 0	160			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 500mA; I _B = 50mA			1.5	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 500mA ; V _{CE} = 5V			1.0	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 160V ; I _E = 0			1.0	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C =0			1.0	μ A
h _{FE}	DC Current Gain	I _C = 100mA ; V _{CE} = 5V	70		240	
C _{OB}	Output Capacitance	I _E = 0 ; V _{CB} = 10V;f= 1.0MHz		25		pF
f _T	Current-Gain—Bandwidth Product	I _C = 100m A ; V _{CE} = 10V		100		MHz

◆ h_{FE} Classifications

O	Y
70-140	120-240

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.