

Silicon NPN Power Transistors

2SC4557

DESCRIPTION


- With TO-3PML package
- High voltage switching transistor

APPLICATIONS

- For switching regulator and general purpose applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter

Absolute maximum ratings($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	900	V
V_{CEO}	Collector-emitter voltage	Open base	550	V
V_{EBO}	Emitter-base voltage	Open collector	7	V
I_C	Collector current		10	A
I_{CM}	Collector current-peak		20	A
I_B	Base current		5	A
P_C	Collector power dissipation	$T_C=25^\circ\text{C}$	80	W
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~150	$^\circ\text{C}$

Silicon NPN Power Transistors

2SC4557

CHARACTERISTICS

Tj=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=10mA$; $R_{BE}=\infty$	550			V
V_{CEsat}	Collector-emitter saturation voltage	$I_C=5A$; $I_B=1A$			0.5	V
V_{BEsat}	Base-emitter saturation voltage	$I_C=5A$; $I_B=1A$			1.2	V
I_{CBO}	Collector cut-off current	$V_{CB}=800V$; $I_E=0$			100	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=7V$; $I_C=0$			100	μA
h_{FE}	DC current gain	$I_C=5A$; $V_{CE}=4V$	10		28	
f_T	Transition frequency	$I_E=-1A$; $V_{CE}=12V$		6		MHz
C_{OB}	Output capacitance	$V_{CB}=10V$; $f=1MHz$		105		pF

Switching times

t_{on}	Turn-on time	$I_C=5A$; $I_{B1}=0.75A$; $I_{B2}=-1.5A$; $R_L=50\Omega$ $V_{CC}=250V$			1.0	μs
t_{stg}	Storage time				5.0	μs
t_f	Fall time				0.5	μs

Silicon NPN Power Transistors

2SC4557

PACKAGE OUTLINE




Fig.2 Outline dimensions

Silicon NPN Power Transistors

2SC4557




Fig.3 Static Characteristic



Fig.4 Base-Emitter Saturation Voltage
Collector-Emitter Saturation Voltage

Fig.5 Safe Operating Area




Fig.6 P_C - T_a DeratingFig.7 I_C - V_{BE} 

Fig.8 DC current Gain